

**INDUSTRIAL COMPONENT DATA**

# T3-4-5/E 020499 Y7-20499 EATON ELECTRIC Multi-speed switches, Contacts: 8, 32 A, One tapped winding, 2 speed..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-4-5/E



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T3-4-5/E        |
| Catalog number  | Y7-20499        |
| Category        | Off-load switch |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-834748705A   |
| Generated       | 2026-08-06      |

## Product Overview

Multi-speed switches, Contacts: 8, 32 A, One tapped winding, 2 speeds, front plate: 2-0-1, 60 °, maintained, flush mounting

Multi-speed switch 8 poles 32 A 1 threaded winding 2

Eaton Moeller® series T3 Multi-speed switches, T3, 32 A, flush mounting, 4 contact unit(s), Contacts: 8, 60 °, maintained, With 0 (Off) position, 2-0-1, Design number 5

Multi-speed switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 8, Degree of Protection: Front IP65, Design: flush mounting, switching function: One tapped winding, 2 speeds, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I<sub>u</sub> = 32 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

## Additional Product Information

**General specifications**

Product Name Eaton Moeller® series T3 Multi-speed switch Catalog Number 020499 Model Code T3-4-5/E EAN 4015080204992 Product Length/Depth 114 mm Product Height 54 mm Product Width 61 mm Product Weight 0.252 kg

Certifications UL Category Control No.: NLRV

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60204

UL File No.: E36332

CE  
CSA-C22.2 No. 94  
UL  
VDE 0660  
IEC/EN 60947  
CSA Class No.: 3211-05  
CSA File No.: 012528  
UL 60947-4-1  
CSA  
IEC/EN 60947-3 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second  
ETIM for 020499 Low-voltage industrial controls and switchgear (EC001105)  
Feature Name  
Feature Value  
Model (EF000010)  
Dahlander switch  
Number of poles (EF001391)  
3  
With zero (off) position (EF001416)  
Yes  
With retraction in 0-position (EF002428)  
No  
Rated permanent current Iu (EF001389)  
32 A  
Rated operation current Ie at AC-3, 400 V (EF001392)  
23.7 A  
Rated operation power at AC-3, 400 V (EF001364)  
12 kW  
Degree of protection (IP), front side (EF003118)  
IP65  
Degree of protection (NEMA), front side (EF011961)  
12  
Number of auxiliary contacts as normally closed contact (EF001377)  
0  
Number of auxiliary contacts as normally open contact (EF001376)  
0  
Number of auxiliary contacts as change-over contact (EF003531)  
0  
Suitable for floor mounting (EF007243)  
No  
Suitable for front mounting (EF007246)  
Yes  
Suitable for distribution board installation (EF007262)  
No  
Suitable for intermediate mounting (EF007264)  
No  
Complete device in housing (EF007317)  
No

Housing materi...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-4-5/E with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.