

INDUSTRIAL COMPONENT DATA

T3-4-8071/XZ 020534 Y7-20534 EATON ELECTRIC Contacts: 8, 32 A, 45 °, rear mounting, Basic switch

Brand: EATON - MOELLER | Manufacturer Part Number: T3-4-8071/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	T3-4-8071/XZ
Catalog number	Y7-20534
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-C804E01C59
Generated	2026-08-04

Product Overview

Contacts: 8, 32 A, 45 °, rear mounting, Basic switch

Switch steps; 8-pole; 32; 45 °; Mounting bottom panel; Switch replacement part for case

T3, 32 A, rear mounting, Basic switch, 4 contact unit(s), Contacts: 8, 45 °, design no. 8071

Measuring point changeover switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204,

Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, Contacts: 8, Design: rear mounting, Basic

switch, Switching angle: 45 °, 4 contact unit(s), Rated uninterrupted current: I_u= 32 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

T3, 32 A, rear mounting, Basic switch, 4 contact unit(s), Contacts: 8, 45 °, design no. 8071Measuring point changeover switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, Contacts: 8, Design: rear mounting, Basic switch, Switching angle: 45 °, 4 contact unit(s), Rated uninterrupted current: I_u= 32 A

Delivery program

Product rangeControl switchesPart group referenceT3Contacts8Designrear mounting

Basic switchContact sequenceSwitching angle45 °Design number8071Front plate no.Motor rating AC-23A, 50 - 60 Hz

[P]400 V [P]15 kWRated uninterrupted current [I_u]32 ANote on rated uninterrupted current !uRated uninterrupted current I_uis specified for max. cross-section.Number of contact units4 contact unit(s)Technical data

GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Open-25 - +50 °C Ambient temperature Enclosed-25 - +40 °C
Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [Uimp] 6000 V AC Mechanical shock resistance 15 g Mounting position As required Contacts Electrical characteristics Rated operational voltage [Ue] 690 V AC
Electrical characteristics Rated uninterrupted current [Iu] 32 A Electrical characteristics Note on rated uninterrupted current
!u Rated uninterrupted current Iuis specified for max. cr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-4-8071/XZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.