

## INDUSTRIAL COMPONENT DATA

**T3-4-88/E 020648 Y7-20648 EATON ELECTRIC****Changeoverswitches, Contacts: 8, 32 A, front plate: 2-0-1, 60 °, ma..**

Brand: EATON - MOELLER | Manufacturer Part Number: T3-4-88/E



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T3-4-88/E       |
| Catalog number  | Y7-20648        |
| Category        | Off-load switch |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-571FAEC5AF   |
| Generated       | 2026-08-04      |

**Product Overview**

Changeoverswitches, Contacts: 8, 32 A, front plate: 2-0-1, 60 °, maintained, flush mounting

Switch Switch; 8-pole; 32; rating Plate: 2-0-1; 60 °; flush Mount

Eaton Moeller® series T3 Changeoverswitches, T3, 32 A, flush mounting, 4 contact unit(s), Contacts: 8, 60 °, maintained, With 0 (Off) position, 2-0-1, Design number 88

Changeover switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 8, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: Iu = 32 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path

EATON - MOELLER &gt; Disconnectors and Cam Switches

**Additional Product Information**

General specifications

Product Name Eaton Moeller® series T3 Changeover switch Catalog Number 020648 Model Code T3-4-88/E EAN 4015080206484 Product Length/Depth 114 mm Product Height 54 mm Product Width 61 mm Product Weight 0.252 kg  
Certifications VDE 0660  
CSA-C22.2 No. 60947-4-1-14

UL  
IEC/EN 60947  
IEC/EN 60204  
UL Category Control No.: NLRV  
UL 60947-4-1  
CSA Class No.: 3211-05  
IEC/EN 60947-3  
CSA  
CE  
CSA File No.: 012528  
UL File No.: E36332  
CSA-C22.2 No. 94 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second  
ETIM for 020648 Low-voltage industrial controls and switchgear (EC001105)  
Feature Name  
Feature Value  
Model (EF000010)  
Reverser  
Number of poles (EF001391)  
4  
With zero (off) position (EF001416)  
Yes  
With retraction in 0-position (EF002428)  
No  
Rated permanent current Iu (EF001389)  
32 A  
Rated operation current Ie at AC-3, 400 V (EF001392)  
23.7 A  
Rated operation power at AC-3, 400 V (EF001364)  
12 kW  
Degree of protection (IP), front side (EF003118)  
IP65  
Degree of protection (NEMA), front side (EF011961)  
12  
Number of auxiliary contacts as normally closed contact (EF001377)  
0  
Number of auxiliary contacts as normally open contact (EF001376)  
0  
Number of auxiliary contacts as change-over contact (EF003531)  
0  
Suitable for floor mounting (EF007243)  
No  
Suitable for front mounting (EF007246)  
Yes  
Suitable for distribution board installation (EF007262)  
No  
Suitable for intermediate mounting (EF007264)  
No

Complete device in housing (EF007317)

No

Housing material (EF00...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-4-88/E with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.