

INDUSTRIAL COMPONENT DATA

T3-5-15892/I2 221642 Y7-221642 EATON ELECTRIC Star-delta switches, Contacts: 10, 32 A, front plate: B 0-Y-D,..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-5-15892/I2



Manufacturer	EATON - MOELLER
MPN / Reference	T3-5-15892/I2
Catalog number	Y7-221642
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-85C9169E82
Generated	2026-08-06

Product Overview

Star-delta switches, Contacts: 10, 32 A, front plate: B>0-Y-D, 60 °, maintained, surface mounting

T3-5-15892/I2

Eaton Moeller® series T3 Star-delta switches, T3, 32 A, surface mounting, 5 contact unit(s), Contacts: 10, 60 °, maintained, With 0 (Off) position, With spring-return to 0, B>0-Y-D, Design number 15892

Star-delta switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 10, Degree of Protection: IP65, Design: surface mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, With spring-return to 0, front plate: B>0-Y-D, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Star-delta switch Catalog Number 221642 Model Code T3-5-15892/I2 EAN 4015082216429 Product Length/Depth 181 mm Product Height 180 mm Product Width 100 mm Product Weight 0.658 kg

Compliances CE Marked Certifications EN 60947-3

UL 508

CSA Std. C22.2 No. 14-05

IEC 60947

VDE

UL

CSA

CSA File No.: 012528

UL Category Control No.: NLRV

UL File No.: E36332

CSA-C22.2 No. 60947-4-1-14

CSA Class No.: 3211-07

VDE 0660

CSA-C22.2 No. 94

IEC/EN 60204

CE

IEC/EN 60947

IEC/EN 60947-3

UL 60947-4-1 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 221642 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Star-delta switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

Yes

Rated permanent current Iu (EF001389)

32 A

Rated operation current Ie at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

18.5 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No
Suitable for in...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-5-15892/I2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.