

INDUSTRIAL COMPONENT DATA

T3-5-8315/E 020704 Y7-20704 EATON ELECTRIC Step switches, Contacts: 9, 32 A, front plate: 0-3, 45 °, maintai..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-5-8315/E



Manufacturer	EATON - MOELLER
MPN / Reference	T3-5-8315/E
Catalog number	Y7-20704
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-8310219AA6
Generated	2026-08-05

Product Overview

Step switches, Contacts: 9, 32 A, front plate: 0-3, 45 °, maintained, flush mounting

Step switch 9 poles 32 A Indicator plate: 0-3 45°

Eaton Moeller® series T3 Step switches, T3, 32 A, flush mounting, 5 contact unit(s), Contacts: 9, 45 °, maintained, With 0 (Off) position, 0-3, Design number 8315

Step switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 9, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-3, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Step switch Catalog Number 020704 Model Code T3-5-8315/E EAN

4015080207047 Product Length/Depth 125 mm Product Height 54 mm Product Width 61 mm Product Weight 0.292 kg

Certifications IEC/EN 60947

UL Category Control No.: NLRV

UL 60947-4-1

CSA File No.: 012528

VDE 0660

CSA Class No.: 3211-05

IEC/EN 60947-3

CSA

CSA-C22.2 No. 94

IEC/EN 60204

UL

UL File No.: E36332

CE

CSA-C22.2 No. 60947-4-1-14 Catalog Notes Rated Short-time Withstand Current (I_{cs}) for a time of 1 second

ETIM for 020704 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reverser

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

32 A

Rated operation current I_e at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material (EF001596...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-5-8315/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.