

## INDUSTRIAL COMPONENT DATA

# T3-5-8315/XZ 020706 Y7-20706 EATON ELECTRIC Serial changeover switch, 3p, Ie 25A, 0-3, 45°, maintained, repl..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-5-8315/XZ



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T3-5-8315/XZ    |
| Catalog number  | Y7-20706        |
| Category        | Off-load switch |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-A2A6902B2C   |
| Generated       | 2026-08-05      |

## Product Overview

Serial changeover switch, 3p, Ie=25A, 0-3, 45°, maintained, replacement switch, base fixing

Step switch 9 poles 20 A Indicator plate: 0-3 45°

T3, 32 A, rear mounting, Basic switch, 5 contact unit(s), Contacts: 9, 45 °, design no. 8315

Step switch, Product range: Control switches, Part group reference: T3, Contacts: 9, Design: rear mounting, Basic switch, Switching angle: 45 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: Iu = 32 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

## Additional Product Information

T3, 32 A, rear mounting, Basic switch, 5 contact unit(s), Contacts: 9, 45 °, design no. 8315Step switch, Product range: Control switches, Part group reference: T3, Contacts: 9, Design: rear mounting, Basic switch, Switching angle: 45 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: Iu = 32 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3Delivery program

Product rangeControl switchesPart group referenceT3Contacts9Designrear mounting

Basic switchContact sequenceSwitching angle45 °Design number8315Front plate no.Motor rating AC-23A, 50 - 60 Hz [P]400 V [P]15 kWRated uninterrupted current [Iu]32 ANote on rated uninterrupted current !uRated uninterrupted current Iuis specified for max. cross-section.Number of contact units5 contact unit(s)Technical data

GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Open-25 - +50 °C Ambient temperature Enclosed-25 - +40 °C  
Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [Uimp] 6000 V AC Mechanical shock resistance 15 g Mounting position As required Contacts Electrical characteristics Rated operational voltage [Ue] 690 V AC  
Electrical characteristics Rated uninterrupted current [Iu] 32 A Electrical characteristics Note on rated uninterrupted current  
!u Rated uninterrupted curre...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-5-8315/XZ with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.