

INDUSTRIAL COMPONENT DATA

T3-6-8615/XZ 004652 Y7-4652 EATON ELECTRIC Multi-speed switches, Contacts: 12, 32 A, 3 speeds, 60 °, rear mo..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-6-8615/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	T3-6-8615/XZ
Catalog number	Y7-4652
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-7D6D6B89DE
Generated	2026-08-05

Product Overview

Multi-speed switches, Contacts: 12, 32 A, 3 speeds, 60 °, rear mounting, Basic switch

Multi-speed switch 12 poles 32 A 3 speeds 60°

Multi-speed switches, T3, 32 A, rear mounting, Basic switch, 6 contact unit(s), Contacts: 12, 60 °, design no. 8615

Multi-speed switch, Product range: Control switches, Part group reference: T3, Contacts: 12, Design: rear mounting, Basic switch, switching function: 3 speeds, Switching angle: 60 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 6 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Multi-speed switches, T3, 32 A, rear mounting, Basic switch, 6 contact unit(s), Contacts: 12, 60 °, design no.

8615Multi-speed switch, Product range: Control switches, Part group reference: T3, Contacts: 12, Design: rear mounting, Basic switch, switching function: 3 speeds, Switching angle: 60 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 6 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204,

Switch-disconnector according to IEC/EN 60947-3Delivery program

Product rangeControl switchesPart group referenceT3Basic functionMulti-speed switchesContacts12Designrear mounting
Basic switchContact sequenceswitching function3 speedsSwitching angle60 °Design number8615Front plate no.Motor
rating AC-23A, 50 - 60 Hz [P]400 V [P]15 kWRated uninterrupted current [I_u]32 ANote on rated uninterrupted current
!I_uRated uninterrupted current I_uis specified for max. cross-section.Number of contact units6 contact unit(s)Technical data

General Standards IEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3 Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Open -25 - +50 °C Ambient temperature Enclosed -25 - +40

°C Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [Uimp] 6000 V AC Mechanical shock

resistance 15 g Mounting position As required Contacts Electrical characteristics Rated operational voltage [Ue] 690 V

AC Electrical characteristics Rat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-6-8615/XZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.