

INDUSTRIAL COMPONENT DATA

T3-7-187/XZ 005504 Y7-5504 EATON ELECTRIC Multi-speed switches, Contacts: 14, 32 A, 3 speeds, 60 °, rear mou..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-7-187/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	T3-7-187/XZ
Catalog number	Y7-5504
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-2D316188A7
Generated	2026-08-05

Product Overview

Multi-speed switches, Contacts: 14, 32 A, 3 speeds, 60 °, rear mounting, Basic switch, SOND 28

Switch Multi-speed; 14-pole; 32; 3 speeds; 60 °; Mounting bottom panel; SOND 28

Multi-speed switches, T3, 32 A, rear mounting, Basic switch, 7 contact unit(s), Contacts: 14, 60 °, SOND 28, design no. 187

Multi-speed switch, Product range: Control switches, Part group reference: T3, Notes: SOND 28, Contacts: 14, Design: rear mounting, Basic switch, switching function: 3 speeds, Switching angle: 60 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 7 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Multi-speed switches, T3, 32 A, rear mounting, Basic switch, 7 contact unit(s), Contacts: 14, 60 °, SOND 28, design no.

187Multi-speed switch, Product range: Control switches, Part group reference: T3, Notes: SOND 28, Contacts: 14, Design: rear mounting, Basic switch, switching function: 3 speeds, Switching angle: 60 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 7 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3Delivery program

Product rangeControl switchesPart group referenceT3Basic functionMulti-speed switchesNotesSOND 28Contacts14Designrear mounting

Basic switchContact sequenceswitching function3 speedsSwitching angle60 °Design number187Front plate no.Motor rating AC-23A, 50 - 60 Hz [P]400 V [P]15 kWRated uninterrupted current [I_u]32 ANote on rated uninterrupted current !uRated

uninterrupted current I_{us} specified for max. cross-section. Number of contact units 7 contact unit(s) Technical data
General Standards IEC/EN 60947, VDE 0660, IEC/EN 60204
Switch-disconnector according to IEC/EN 60947-3 Climatic proofing Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Open -25 - +50 °C Ambient temperature Enclosed -25 - +40
°C Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [U_{imp}] 6000 V AC Mechanical shock
resistance 15 g Mounting position As required Contacts Electrical characteristics Rated operational voltage [U_e] 69...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-7-187/XZ with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.