


INDUSTRIAL COMPONENT DATA

T5-2-37/Z 096850 Y7-96850 EATON ELECTRIC Multi-speed switches, Contacts: 4, 100 A, 2 speeds, front plate: 2-..

Brand: EATON - MOELLER | Manufacturer Part Number: T5-2-37/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T5-2-37/Z
Catalog number	Y7-96850
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-9249B4C6F8
Generated	2026-08-05

Product Overview

Multi-speed switches, Contacts: 4, 100 A, 2 speeds, front plate: 2-0-1, 60 °, maintained, rear mounting

Multi-speed switch 4 poles 100 A 2 speed Plate

Eaton Moeller® series T5 Multi-speed switches, T5, 100 A, rear mounting, 2 contact unit(s), Contacts: 4, 60 °, maintained, With 0 (Off) position, 2-0-1, Design number 37

Multi-speed switch, Product range: Control switches, Part group reference: T5, with black thumb grip and front plate, Contacts: 4, Degree of Protection: Front IP65, Design: rear mounting, switching function: 2 speeds, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 55 kW, Rated uninterrupted current: I_u = 100 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5 Multi-speed switch Catalog Number 096850 Model Code T5-2-37/Z EAN 4015080968504 Product Length/Depth 149 mm Product Height 88 mm Product Width 88 mm Product Weight 0.488 kg

Certifications IEC/EN 60204

VDE 0660

IEC/EN 60947

IEC/EN 60947-3 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 096850 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reverser

Number of poles (EF001391)

2

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

100 A

Rated operation current I_e at AC-3, 400 V (EF001392)

55 A

Rated operation power at AC-3, 400 V (EF001364)

30 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007317)

No

Housing material (EF001596)

Plastic

Type of control element (EF006976)

Short thumb-grip

Type of electrical connection of main circuit (EF006819)

Screw connection

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5-2-37/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.