

## INDUSTRIAL COMPONENT DATA

**T5-3-8342/X 096379 Y7-96379 EATON ELECTRIC On-Off switch, 6 pole, 100 A, 90 °, rear mounting, Basic switch**

Brand: EATON - MOELLER | Manufacturer Part Number: T5-3-8342/X



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | T5-3-8342/X         |
| Catalog number  | Y7-96379            |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-BF88824F96       |
| Generated       | 2026-08-03          |

**Product Overview**

On-Off switch, 6 pole, 100 A, 90 °, rear mounting, Basic switch

Disconnecter switch ON-OFF; 6 poles; 100 A; 90 °; Switch

Eaton Moeller® series T5 On-Off switch, T5, 100 A, rear mounting, Basic switch, 3 contact unit(s), 6 pole

On-Off switch, Product range: On-Off switch, Part group reference: T5, 6 pole, Design: rear mounting, Basic switch,

Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 55 kW, Rated uninterrupted current: I<sub>u</sub> = 100 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

**Additional Product Information**

## General specifications

Product Name Eaton Moeller® series T5 On-off switch Catalog Number 096379 Model Code T5-3-8342/X EAN 4015080963790 Product Length/Depth 113 mm Product Height 85 mm Product Width 85 mm Product Weight 0.55 kg

Certifications IEC/EN 60947

IEC/EN 60204

VDE 0660

IEC/EN 60947-3 Catalog Notes Rated Short-time Withstand Current (I<sub>cw</sub>) for a time of 1 second

ETIM for 096379 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)  
No  
Version as maintenance-/service switch (EF006986)  
No  
Version as safety switch (EF006985)  
No  
Version as emergency stop installation (EF006959)  
No  
Version as reversing switch (EF009408)  
No  
Number of switches (EF005586)  
1  
Max. rated operation voltage  $U_e$  AC (EF007355)  
690 V  
Rated operating voltage (EF001435)  
690 V  
Rated permanent current  $I_u$  (EF001389)  
100 A  
Rated permanent current at AC-21, 400 V (EF009165)  
100 A  
Rated operation power at AC-3, 400 V (EF001364)  
30 kW  
Rated short-time withstand current  $I_{cw}$  (EF007050)  
1.7 kA  
Rated operation power at AC-23, 400 V (EF007027)  
55 kW  
Switching power at 400 V (EF009166)  
55 kW  
Conditioned rated short-circuit current  $I_q$  (EF001444)  
2 kA  
Number of poles (EF001391)  
6  
Number of auxiliary contacts as normally closed contact (EF001377)  
0  
Number of auxiliary contacts as normally open contact (EF001376)  
0  
Number of auxiliary contacts as change-over contact (EF003531)  
0  
Motor drive optional (EF007386)  
No  
Motor drive integrated (EF006697)  
No  
Voltag...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5-3-8342/X with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.