

INDUSTRIAL COMPONENT DATA

T5-4-15164/ST/SVB 081952 EATON ELECTRIC Main switch, +steel enclosure, 6p+1N/O+1N/C, Ie 80A, handle red yell..

Brand: EATON - MOELLER | Manufacturer Part Number: T5-4-15164/ST/SVB



Manufacturer	EATON - MOELLER
MPN / Reference	T5-4-15164/ST/SVB
Catalog number	081952
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-0B0E875E0C
Generated	2026-08-06

Product Overview

Main switch, +steel enclosure, 6p+1N/O+1N/C, Ie=80A, handle red yellow, 0-1, 90°

General switch; Mounting stainless steel box; 6-pole + 1 NO + 1 NC; 80A; Control Red/Yellow; 0-1; 90°

Main switch according to IEC/EN60947-3, size T5 in steel sheet enclosure, 690 V/100A, degree of protection Front IP65, lockable in O position with 3 padlocks, design general: insulating material-surface mounting enclosure, flush mounting breaker. High-performance, robust, compact T cam switches are used in industry, the trades, and building services management. A variety of standard switches is available for selection. These are supplemented by special customer-specific switches. Here the possibilities are almost unlimited. Comprehensive accessories complete the switch product range and supplement the usage alternatives. All current paths are equipped with double-break contacts.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Main switch, +steel enclosure, 6p+1N/O+1N/C, Ie=80A, handle red yellow, 0-1, 90°Main switch according to IEC/EN60947-3, size T5 in steel sheet enclosure, 690 V/100A, degree of protection Front IP65, lockable in O position with 3 padlocks, design general: insulating material-surface mounting enclosure, flush mounting breaker. High-performance, robust, compact T cam switches are used in industry, the trades, and building services management. A variety of standard switches is available for selection. These are supplemented by special customer-specific switches. Here the possibilities are almost unlimited. Comprehensive accessories complete the switch product range and supplement the usage alternatives. All current paths are equipped with double-break contacts.Delivery program
Product rangeMain switch

maintenance switch

Repair switchPart group referenceT5Stop FunctionEmergency switching off functionWith red rotary handle and yellow locking ringNumber of poles6 poleAuxiliary contacts1 N/O1 N/CDegree of ProtectionIP65Designsurface mountingContact sequenceDesign number15164FunctionMotor rating AC-23A, 50 - 60 Hz [P]400 V [P]55 kWRated uninterrupted current [Iu]100 ANote on rated uninterrupted current !uRated uninterrupted current Iuis specified for max. cross-section.Number of contact units4 contact unit(s)Technical data
GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204
Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78
Damp h...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5-4-15164/ST/SVB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.