

INDUSTRIAL COMPONENT DATA

T5-4-15700/X 096081 Y7-96081 EATON ELECTRIC On-Off switch, 6 pole + 2 N/O, 100 A, 90 °, rear mounting, Basic..

Brand: EATON - MOELLER | Manufacturer Part Number: T5-4-15700/X



Manufacturer	EATON - MOELLER
MPN / Reference	T5-4-15700/X
Catalog number	Y7-96081
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-89B0521814
Generated	2026-08-04

Product Overview

On-Off switch, 6 pole + 2 N/O, 100 A, 90 °, rear mounting, Basic switch

Disconnect switch ON-OFF; 6-pole + 2 NO; 100 A; 90 °; Mounting bottom panel; Switch replacement part for case Eaton Moeller® series T5 On-Off switch, T5, 100 A, rear mounting, Basic switch, 4 contact unit(s), 6 pole, 2 N/O On-Off switch, Product range: On-Off switch, Part group reference: T5, 6 pole, Design: rear mounting, Basic switch, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 55 kW, Rated uninterrupted current: I_u = 100 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5 On-off switch Catalog Number 096081 Model Code T5-4-15700/X EAN 4015080960812 Product Length/Depth 130 mm Product Height 85 mm Product Width 85 mm Product Weight 0.682 kg Certifications VDE 0660

IEC/EN 60204

IEC/EN 60947

IEC/EN 60947-3 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 096081 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)
No
Version as maintenance-/service switch (EF006986)
No
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
No
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Rated operating voltage (EF001435)
690 V
Rated permanent current I_u (EF001389)
100 A
Rated permanent current at AC-21, 400 V (EF009165)
100 A
Rated operation power at AC-3, 400 V (EF001364)
30 kW
Rated short-time withstand current I_{cw} (EF007050)
1.7 kA
Rated operation power at AC-23, 400 V (EF007027)
55 kW
Switching power at 400 V (EF009166)
55 kW
Conditioned rated short-circuit current I_q (EF001444)
2 kA
Number of poles (EF001391)
6
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
2
Number of auxiliary contacts as change-over contact (EF003531)
0
Motor drive optional (EF007386)
No
Motor drive integrated (EF006697)
No
Voltage release optional (EF007491)
No
Device constructi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5-4-15700/X with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.