

INDUSTRIAL COMPONENT DATA

T5-6-15252/X 094878 Y7-94878 EATON ELECTRIC Step switch, 1p, 1e 80A, 1-11, 30°, maintained, replacement swit..

Brand: EATON - MOELLER | Manufacturer Part Number: T5-6-15252/X



Manufacturer	EATON - MOELLER
MPN / Reference	T5-6-15252/X
Catalog number	Y7-94878
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-3653ABF2B3
Generated	2026-08-03

Product Overview

Step switch, 1p, 1e=80A, 1-11, 30°, maintained, replacement switch

Step Switch 1 Pole 80 A Indicator Plate: 1-11 30°

T5, 100 A, rear mounting, Basic switch, 6 contact unit(s), Contacts: 11, 30 °, design no. 15252

Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T5, Contacts: 11, Design: rear mounting, Basic switch, Switching angle: 30 °, 6 contact unit(s), Rated uninterrupted current: I_u= 100 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

T5, 100 A, rear mounting, Basic switch, 6 contact unit(s), Contacts: 11, 30 °, design no. 15252 Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T5, Contacts: 11, Design: rear mounting, Basic switch, Switching angle: 30 °, 6 contact unit(s), Rated uninterrupted current: I_u= 100 A Delivery program

Product range Control switches Part group reference T5 Contacts 11 Design rear mounting

Basic switch Contact sequence Switching angle 30 ° Design number 15252 Front plate no. Motor rating AC-23A, 50 - 60 Hz [P]400 V [P]55 kW Rated uninterrupted current [I_u]100 A Note on rated uninterrupted current !I_u Rated uninterrupted current I_u is specified for max. cross-section. Number of contact units 6 contact unit(s) Technical data

General Standards IEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3 Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Open-25 - +50 °C Ambient temperature Enclosed-25 - +40 °C
Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [Uimp] 6000 V AC Mechanical shock resistance 15 g Mounting position As required Contacts Electrical characteristics Rated operational voltage [Ue] 690 V AC
Electrical characteristics Rated uninterrupted current [Iu] 100 A Electrical characteristics Note on rated uninterrupted current Iu Rated uninterrupted current Iuis specified for max. cross-section. L...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5-6-15252/X with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.