

INDUSTRIAL COMPONENT DATA

T5-7-8371/E 094655 Y7-94655 EATON ELECTRIC

Changeoverswitches, Contacts: 14, 100 A, front plate: 1-2, 90 °, ..

Brand: EATON - MOELLER | Manufacturer Part Number: T5-7-8371/E



Manufacturer	EATON - MOELLER
MPN / Reference	T5-7-8371/E
Catalog number	Y7-94655
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-447DF89C50
Generated	2026-08-04

Product Overview

Changeoverswitches, Contacts: 14, 100 A, front plate: 1-2, 90 °, maintained, flush mounting

Switch Switch; 14 poles; 100 A; Indicator plate: 1-2; 90 °;

Eaton Moeller® series T5 Changeoverswitches, T5, 100 A, flush mounting, 7 contact unit(s), Contacts: 14, 90 °, maintained, Without 0 (Off) position, 1-2, Design number 8371

Changeover switch, Product range: Control switches, Part group reference: T5, with black thumb grip and front plate, Contacts: 14, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Switching performance: maintained, Without 0 (Off) position, front plate: 1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 55 kW, Rated uninterrupted current: I_u = 100 A, 7 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5 Changeover switch Catalog Number 094655 Model Code T5-7-8371/E EAN 4015080946557 Product Length/Depth 190 mm Product Height 88 mm Product Width 88 mm Product Weight 1.13 kg

Certifications IEC/EN 60947

IEC/EN 60947-3

VDE 0660

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 094655 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reverser

Number of poles (EF001391)

7

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

100 A

Rated operation current I_e at AC-3, 400 V (EF001392)

55 A

Rated operation power at AC-3, 400 V (EF001364)

30 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material (EF001596)

Plastic

Type of control element (EF006976)

Short thumb-grip

Type of electrical connection of main circuit (EF006819)

Screw connection

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5-7-8371/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.