

INDUSTRIAL COMPONENT DATA

T5B-2-10/EA/SVB 094118 Y7-94118 EATON ELECTRIC Main switch, 3 pole + N, 63 A, Emergency-Stop function, 90 °,..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-2-10/EA/SVB



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-2-10/EA/SVB
Catalog number	Y7-94118
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-3AD148E08E
Generated	2026-08-03

Product Overview

Main switch, 3 pole + N, 63 A, Emergency-Stop function, 90 °, flush mounting

General switch; 3-pole + N; 63; Handle Red/Yellow; 90 °; Mounting

Eaton Moeller® series T5B Main switch, T5B, 63 A, flush mounting, 2 contact unit(s), 3 pole + N, Emergency switching off function, With red rotary handle and yellow locking ring

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T5B, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, 3 pole + N, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Main switch Catalog Number 094118 Model Code T5B-2-10/EA/SVB EAN 4015080941187 Product Length/Depth 140 mm Product Height 88 mm Product Width 88 mm Product Weight 0.605 kg

Certifications CSA

CSA Class No.: 3211-05

CSA File No.: 012528

UL File No.: E36332

CE
UL
IEC/EN 60947
VDE 0660
UL 60947-4-1
UL Category Control No.: NLRV
CSA-C22.2 No. 60947-4-1-14
CSA-C22.2 No. 94
IEC/EN 60947-3
IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 094118 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as main switch (EF006981)
Yes
Version as maintenance-/service switch (EF006986)
Yes
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
Yes
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Rated operating voltage (EF001435)
690 V
Rated permanent current Iu (EF001389)
63 A
Rated permanent current at AC-21, 400 V (EF009165)
63 A
Rated operation power at AC-3, 400 V (EF001364)
22 kW
Rated short-time withstand current Icw (EF007050)
1.3 kA
Rated operation power at AC-23, 400 V (EF007027)
30 kW
Switching power at 400 V (EF009166)
30 kW
Conditioned rated short-circuit current Iq (EF001444)
2 kA
Number of poles (EF001391)
4
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0

Number of auxiliary contacts....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-2-10/EA/SVB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.