

## INDUSTRIAL COMPONENT DATA

**T5B-3-123/E 092850 Y7-92850 EATON ELECTRIC Reversing switches, Contacts: 6, 63 A, front plate: 2-0-1, 90 °, ..**

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-3-123/E



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T5B-3-123/E     |
| Catalog number  | Y7-92850        |
| Category        | Off-load switch |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-99B3875976   |
| Generated       | 2026-08-06      |

**Product Overview**

Reversing switches, Contacts: 6, 63 A, front plate: 2-0-1, 90 °, maintained, flush mounting, SOND 30

Reversing switch; 6-pole; 63; rating Plate: 2-0-1; 90 °; Latch; flush Mount; SOND 30

Eaton Moeller® series T5B Reversing switches, T5B, 63 A, flush mounting, 3 contact unit(s), Contacts: 6, 60 °, maintained, With 0 (Off) position, 2-0-1, SOND 30, Design number 123

Reversing switch, Product range: Control switches, Part group reference: T5B, with black thumb grip and front plate, Notes: SOND 30, Contacts: 6, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

**Additional Product Information**

## General specifications

Product Name Eaton Moeller® series T5B Reversing switch Catalog Number 092850 Model Code T5B-3-123/E EAN 4015080928508 Product Length/Depth 124 mm Product Height 88 mm Product Width 88 mm Product Weight 0.59 kg

Certifications IEC/EN 60204

IEC/EN 60947

UL Category Control No.: NLRV

CSA File No.: 012528

CSA-C22.2 No. 60947-4-1-14

CSA-C22.2 No. 94

UL 60947-4-1

CSA

CSA Class No.: 3211-07

IEC/EN 60947-3

UL File No.: E36332

UL

VDE 0660

CE Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 092850 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reversing switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

63 A

Rated operation current Ie at AC-3, 400 V (EF001392)

41 A

Rated operation power at AC-3, 400 V (EF001364)

22 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing materia...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-3-123/E with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.