

**INDUSTRIAL COMPONENT DATA**

# T5B-3-15159/I4/SVB 222978 Y7-222978 EATON ELECTRIC

## Main switch, 3 pole, 25 A, rear mounting

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-3-15159/I4/SVB



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | T5B-3-15159/I4/SVB  |
| Catalog number  | Y7-222978           |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-7A03012374       |
| Generated       | 2026-08-03          |

### Product Overview

Main switch, 3 pole, 25 A, rear mounting

T5B-3-15159/I4/SVB

Eaton Moeller® series T5B Main switch, T5B, 63 A, surface mounting, 3 contact unit(s), 3 pole, 2 N/O, 1 N/C, Emergency switching off function, With red rotary handle and yellow locking ring

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T5B, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, 3 pole, Degree of Protection: IP65, Design: surface mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

### Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Main switch Catalog Number 222978 Model Code T5B-3-15159/I4/SVB EAN 4015082229788 Product Length/Depth 240 mm Product Height 204 mm Product Width 160 mm Product Weight 1.358 kg

Certifications CSA-C22.2 No. 94

CSA Class No.: 3211-07

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

UL  
CE  
IEC/EN 60204  
CSA File No.: 012528  
VDE 0660  
CSA  
IEC/EN 60947  
UL Category Control No.: NLRV  
IEC/EN 60947-3  
UL File No.: E36332 Catalog Notes Rated Short-time Withstand Current (I<sub>cw</sub>) for a time of 1 second  
ETIM for 222978 Low-voltage industrial controls and switchgear (EC000216)

| Feature Name                                                       | Feature Value |
|--------------------------------------------------------------------|---------------|
| Version as main switch (EF006981)                                  | Yes           |
| Version as maintenance-/service switch (EF006986)                  | Yes           |
| Version as safety switch (EF006985)                                | No            |
| Version as emergency stop installation (EF006959)                  | Yes           |
| Version as reversing switch (EF009408)                             | No            |
| Number of switches (EF005586)                                      | 1             |
| Rated operating voltage (EF001435)                                 | 690 V         |
| Rated permanent current I <sub>u</sub> (EF001389)                  | 63 A          |
| Rated permanent current at AC-23, 400 V (EF011777)                 | 63 A          |
| Rated permanent current at AC-21, 400 V (EF009165)                 | 63 A          |
| Rated operation power at AC-3, 400 V (EF001364)                    | 22 kW         |
| Rated short-time withstand current I <sub>cw</sub> (EF007050)      | 1.3 kA        |
| Rated operation power at AC-23, 400 V (EF007027)                   | 30 kW         |
| Switching power at 400 V (EF009166)                                | 30 kW         |
| Conditioned rated short-circuit current I <sub>q</sub> (EF001444)  | 2 kA          |
| Number of poles (EF001391)                                         | 3             |
| Number of auxiliary contacts as normally closed contact (EF001377) | 1             |

Number of auxiliary contacts as nor...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-3-15159/I4/SVB with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.