

INDUSTRIAL COMPONENT DATA

T5B-3-15159/I4/SVB 222978 Y7-222978 EATON ELECTRIC

Main switch, 3 pole, 25 A, rear mounting

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-3-15159/I4/SVB



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-3-15159/I4/SVB
Catalog number	Y7-222978
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-7A03012374
Generated	2026-08-05

Product Overview

Main switch, 3 pole, 25 A, rear mounting

T5B-3-15159/I4/SVB

Eaton Moeller® series T5B Main switch, T5B, 63 A, surface mounting, 3 contact unit(s), 3 pole, 2 N/O, 1 N/C, Emergency switching off function, With red rotary handle and yellow locking ring

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T5B, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, 3 pole, Degree of Protection: IP65, Design: surface mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Main switch Catalog Number 222978 Model Code T5B-3-15159/I4/SVB EAN 4015082229788 Product Length/Depth 240 mm Product Height 204 mm Product Width 160 mm Product Weight 1.358 kg

Certifications CSA-C22.2 No. 94

CSA Class No.: 3211-07

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

UL
CE
IEC/EN 60204
CSA File No.: 012528
VDE 0660
CSA
IEC/EN 60947
UL Category Control No.: NLRV
IEC/EN 60947-3
UL File No.: E36332 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second
ETIM for 222978 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as main switch (EF006981)
Yes
Version as maintenance-/service switch (EF006986)
Yes
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
Yes
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Rated operating voltage (EF001435)
690 V
Rated permanent current I_u (EF001389)
63 A
Rated permanent current at AC-23, 400 V (EF011777)
63 A
Rated permanent current at AC-21, 400 V (EF009165)
63 A
Rated operation power at AC-3, 400 V (EF001364)
22 kW
Rated short-time withstand current I_{cw} (EF007050)
1.3 kA
Rated operation power at AC-23, 400 V (EF007027)
30 kW
Switching power at 400 V (EF009166)
30 kW
Conditioned rated short-circuit current I_q (EF001444)
2 kA
Number of poles (EF001391)
3
Number of auxiliary contacts as normally closed contact (EF001377)
1

Number of auxiliary contacts as nor...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-3-15159/I4/SVB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.