

INDUSTRIAL COMPONENT DATA

T5B-3-15453/X 092452 Y7-92452 EATON ELECTRIC
Changeover switch, 1p, Ie 63A, UPS NETWORK, 90°,
maintained, re..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-3-15453/X



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-3-15453/X
Catalog number	Y7-92452
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-09A040B2A7
Generated	2026-08-05

Product Overview

Changeover switch, 1p, Ie=63A, UPS NETWORK, 90°, maintained, replacement switch

Switch 1-pole 63 A Switch Indicator Plate: Hand-AUTO 90°

T5B, 63 A, rear mounting, Basic switch, 3 contact unit(s), Contacts: 6, 90 °, HAND-AUTO, design no. 15453

Changeover switch, Product range: Control switches, Part group reference: T5B, Contacts: 6, Design: rear mounting, Basic switch, Switching angle: 90 °, front plate: HAND-AUTO, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

T5B, 63 A, rear mounting, Basic switch, 3 contact unit(s), Contacts: 6, 90 °, HAND-AUTO, design no. 15453Changeover switch, Product range: Control switches, Part group reference: T5B, Contacts: 6, Design: rear mounting, Basic switch, Switching angle: 90 °, front plate: HAND-AUTO, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3Delivery program

Product rangeControl switchesPart group referenceT5BContacts6Designrear mounting

Basic switchContact sequenceSwitching angle90 °Design number15453Front plate no.front plateHAND-AUTOMotor rating

AC-23A, 50 - 60 Hz [P]400 V [P]30 kW Rated uninterrupted current [I_u]63 A Note on rated uninterrupted current I_u Rated uninterrupted current I_u is specified for max. cross-section. Number of contact units 3 contact unit(s) Technical data General Standards IEC/EN 60947, VDE 0660, IEC/EN 60204 Switch-disconnector according to IEC/EN 60947-3 Climatic proofing Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Open -25 - +50 °C Ambient temperature Enclosed -25 - +40 °C Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [U_{imp}]6000 V AC Mechanical shock resistance 15 g Mounting position As required Contacts Electrical characteristics Rated operational voltage [U_e]690 V AC Electrical characteristics Rated uninterrupted current [I_u]63 A Electrical characterist...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-3-15453/X with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.