

INDUSTRIAL COMPONENT DATA

T5B-3-7/I4 222554 Y7-222554 EATON ELECTRIC Multi-speed switches, Contacts: 6, 63 A, 2 speeds, front plate: 2..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-3-7/I4



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-3-7/I4
Catalog number	Y7-222554
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-63318FF428
Generated	2026-08-05

Product Overview

Multi-speed switches, Contacts: 6, 63 A, 2 speeds, front plate: 2-0-1, 60 °, maintained, surface mounting
T5B-3-7/I4

Multi-speed switches, T5B, 63 A, surface mounting, 3 contact unit(s), Contacts: 6, 60 °, maintained, With 0 (Off) position, 2-0-1, Design number 7

Multi-speed switch, Product range: Control switches, Part group reference: T5B, with black thumb grip and front plate, Contacts: 6, Degree of Protection: IP65, Design: surface mounting, switching function: 2 speeds, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Multi-speed switches, T5B, 63 A, surface mounting, 3 contact unit(s), Contacts: 6, 60 °, maintained, With 0 (Off) position, 2-0-1, Design number 7Multi-speed switch, Product range: Control switches, Part group reference: T5B, with black thumb grip and front plate, Contacts: 6, Degree of Protection: IP65, Design: surface mounting, switching function: 2 speeds, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

General specificationsProduct nameEaton Moeller® series T5B Multi-speed switchPart

no.T5B-3-7/I4EAN4015082225544Product Length/Depth240 millimetreProduct height197 millimetreProduct width160 millimetreProduct weight1.303 kilogramCertificationsCSA

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60204

UL

IEC/EN 60947-3

UL 60947-4-1

IEC/EN 60947

CSA Class No.: 3211-07

VDE 0660

UL Category Control No.: NLRV

CE

CSA-C22.2 No. 94

UL File No.: E36332

CSA File No.: 012528Product TradenameT5BProduct TypeMulti-speed switchProduct Sub TypeNoneCatalog NotesRated Short-time Withstand Current (Icw) for a time of 1 secondFeatures & FunctionsEnclosure materialPlasticFeaturesComplete device in housingFitted with:0 (off) position

Black thumb grip and front plateInscription2-0-1Number of poles3Switch function type2 speedsGeneral informationDeg...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-3-7/I4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.