

**INDUSTRIAL COMPONENT DATA**

# T5B-4-15164/EA/SVB 092230 Y7-92230 EATON ELECTRIC

## Main switch, 6 pole + 1 N/O + 1 N/C, 63 A, Emergency-Stop ..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-4-15164/EA/SVB



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | T5B-4-15164/EA/SVB  |
| Catalog number  | Y7-92230            |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-55E58C6503       |
| Generated       | 2026-08-03          |

### Product Overview

Main switch, 6 pole + 1 N/O + 1 N/C, 63 A, Emergency-Stop function, 90 °, flush mounting

General Switch 6 poles + N + 1 NO + 1 NC 63 A 90° Mounting

Eaton Moeller® series T5B Main switch, T5B, 63 A, flush mounting, 4 contact unit(s), 6 pole, 1 N/O, 1 N/C, Emergency switching off function, With red rotary handle and yellow locking ring

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T5B, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, 6 pole, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                                  |
|--------------|--------------------------------------------------|
| Catalog path | EATON - MOELLER > Disconnectors and Cam Switches |
|--------------|--------------------------------------------------|

### Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Main switch Catalog Number 092230 Model Code T5B-4-15164/EA/SVB EAN 4015080922308 Product Length/Depth 173 mm Product Height 88 mm Product Width 88 mm Product Weight 0.951 kg

Certifications UL 60947-4-1

CE

CSA File No.: 012528

CSA

CSA-C22.2 No. 60947-4-1-14

UL Category Control No.: NLRV

VDE 0660

CSA Class No.: 3211-05

IEC/EN 60204

IEC/EN 60947-3

IEC/EN 60947

UL

CSA-C22.2 No. 94

UL File No.: E36332 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 092230 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

Yes

Version as maintenance-/service switch (EF006986)

Yes

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

Yes

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Rated operating voltage (EF001435)

690 V

Rated permanent current Iu (EF001389)

63 A

Rated permanent current at AC-21, 400 V (EF009165)

63 A

Rated operation power at AC-3, 400 V (EF001364)

22 kW

Rated short-time withstand current Icw (EF007050)

1.3 kA

Rated operation power at AC-23, 400 V (EF007027)

30 kW

Switching power at 400 V (EF009166)

30 kW

Conditioned rated short-circuit current Iq (EF001444)

2 kA

Number of poles (EF001391)

6

Number of auxiliary contacts as normally closed contact (EF001377)

1

Number of auxiliary contacts as normally open contact (EF001376)

1

Number of auxiliary contac...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-4-15164/EA/SVB with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.