

INDUSTRIAL COMPONENT DATA

T5B-4-24/Z 092161 Y7-92161 EATON ELECTRIC Star-delta switches, Contacts: 7, 63 A, front plate: 0-Y-D, 60 °, ..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-4-24/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-4-24/Z
Catalog number	Y7-92161
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-A874C586AB
Generated	2026-08-06

Product Overview

Star-delta switches, Contacts: 7, 63 A, front plate: 0-Y-D, 60 °, maintained, rear mounting, SOND 29
Switch Star-delta; 7-pole; 63; rating Plate: 0 -, And-D; 60 °; Interlocking; Installation bottom panel; SOND 29
Eaton Moeller® series T5B Star-delta switches, T5B, 63 A, rear mounting, 4 contact unit(s), Contacts: 7, 60 °, maintained, With 0 (Off) position, 0-Y-D, SOND 29, Design number 24
Star-delta switch, Product range: Control switches, Part group reference: T5B, with black thumb grip and front plate, Notes: SOND 29, Contacts: 7, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-Y-D, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Star-delta switch Catalog Number 092161 Model Code T5B-4-24/Z EAN 4015080921615 Product Length/Depth 182 mm Product Height 88 mm Product Width 88 mm Product Weight 0.769 kg

Certifications UL

UL File No.: E36332

UL 60947-4-1

CSA

CSA Class No.: 3211-05

UL Category Control No.: NLRV

CSA File No.: 012528

IEC/EN 60204

CSA-C22.2 No. 94

VDE 0660

CSA-C22.2 No. 60947-4-1-14

CE

IEC/EN 60947

IEC/EN 60947-3 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 092161 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Star-delta switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

63 A

Rated operation current Ie at AC-3, 400 V (EF001392)

41 A

Rated operation power at AC-3, 400 V (EF001364)

37 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007317)

No

Housing mate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-4-24/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.