

INDUSTRIAL COMPONENT DATA

T5B-4-88/I4 223025 Y7-223025 EATON ELECTRIC

Changeoverswitches, Contacts: 8, 63 A, front plate: 2-0-1, 60 °, ..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-4-88/I4



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-4-88/I4
Catalog number	Y7-223025
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-6B56E31B27
Generated	2026-08-06

Product Overview

Changeoverswitches, Contacts: 8, 63 A, front plate: 2-0-1, 60 °, maintained, surface mounting

T5B-4-88/I4

Eaton Moeller® series T5B Changeoverswitches, T5B, 63 A, surface mounting, 4 contact unit(s), Contacts: 8, 60 °, maintained, With 0 (Off) position, 2-0-1, Design number 88

Changeover switch, Product range: Control switches, Part group reference: T5B, with black thumb grip and front plate, Contacts: 8, Degree of Protection: IP65, Design: surface mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Changeover switch Catalog Number 223025 Model Code T5B-4-88/I4 EAN 4015082230258 Product Length/Depth 240 mm Product Height 197 mm Product Width 160 mm Product Weight 1.435 kg

Certifications CSA-C22.2 No. 94

UL Category Control No.: NLRV

UL 60947-4-1
CSA Class No.: 3211-07
IEC/EN 60204
CSA-C22.2 No. 60947-4-1-14
IEC/EN 60947
CSA
IEC/EN 60947-3
UL
CE
UL File No.: E36332
CSA File No.: 012528
VDE 0660 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 223025 Low-voltage industrial controls and switchgear (EC001105)
Feature Name
Feature Value
Model (EF000010)
Reverser
Number of poles (EF001391)
4
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
No
Rated permanent current Iu (EF001389)
63 A
Rated operation current Ie at AC-3, 400 V (EF001392)
41 A
Rated operation power at AC-3, 400 V (EF001364)
22 kW
Degree of protection (IP), front side (EF003118)
IP65
Degree of protection (NEMA), front side (EF011961)
12
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
0
Suitable for floor mounting (EF007243)
Yes
Suitable for front mounting (EF007246)
No
Suitable for distribution board installation (EF007262)
No
Suitable for intermediate mounting (EF007264)
No

Complete device in housing (EF007317)

Yes

Housing material (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-4-88/I4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.