

INDUSTRIAL COMPONENT DATA

T5B-5-15247/E 091971 Y7-91971 EATON ELECTRIC Step switches, Contacts: 9, 63 A, front plate: 0-9, 30 °, maint..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-5-15247/E



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-5-15247/E
Catalog number	Y7-91971
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-F8695E3058
Generated	2026-08-04

Product Overview

Step switches, Contacts: 9, 63 A, front plate: 0-9, 30 °, maintained, flush mounting
Switch steps; 9-pole; 63; Plate indicator: 0-9; 30 °; Interlock; recessed Mounting
Eaton Moeller series T5B Step switch, 63 A, Flush mounting, 5 contact unit(s), Contacts: 9, Maintained, 0-9, Design: 15247
Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL,
Switch-disconnector according to IEC/EN 60947-3, Part group reference: T5B, with black thumb grip and front plate,
Contacts: 9, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 30 °, Switching performance:
maintained, With 0 (Off) position, 5 contact unit(s), Rated uninterrupted current: Iu= 63 A, front plate: 0-9

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications
Product Name Eaton Moeller® series T5B Step switch
Catalog Number 091971
Model Code T5B-5-15247/E
EAN 4015080919711
Product Length/Depth 157 mm
Product Height 88 mm
Product Width 88 mm
Product Weight 0.86 kg

Certifications UL Category Control No.: NLRV

CSA File No.: 012528

UL File No.: E36332

CSA

IEC/EN 60204

UL

UL 60947-4-1

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947

VDE 0660

CSA-C22.2 No. 94

CE

CSA Class No.: 3211-07

IEC/EN 60947-3

Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

Features & Functions

Fitted with: Black thumb grip and front plate

0 (off) position

Inscription 0-9

Number of poles Single-pole

General information

Degree of protection IP65

NEMA 12

NEMA 1

Degree of protection (front side) IP65

NEMA 12

Lifespan, mechanical 500,000 Operations

Mounting method Flush mounting

Mounting position As required

Number of contact units 5

Operating frequency 1200 Operations/h

Overvoltage category III

Pollution degree 3

Product category Control switches

Product category Control switches

Rated impulse withstand voltage (Uimp) 6000 V AC

Safe isolation 440 V AC, Between the contacts, According to EN 61140

Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1

Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms

Suitable for Branch circuits, suitable as motor disconnect, (UL/CSA)

Front mounting

Switching angle 30 °

Type Step switch

Climatic environmental conditions

Amb...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-5-15247/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.