

INDUSTRIAL COMPONENT DATA

T5B-5-15896/E 091953 Y7-91953 EATON ELECTRIC Reversing star-delta switches, Contacts: 10, 63 A, front plate:..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-5-15896/E



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-5-15896/E
Catalog number	Y7-91953
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-E4095F7A38
Generated	2026-08-05

Product Overview

Reversing star-delta switches, Contacts: 10, 63 A, front plate: D-Y-0-Y-D, 60 °, maintained, flush mounting

Star-Triangle switch with inversion. 10 poles. 63 A. Plate

Eaton Moeller® series T5B Reversing star-delta switches, T5B, 63 A, flush mounting, 5 contact unit(s), Contacts: 10, 60 °, maintained, With 0 (Off) position, D-Y-0-Y-D, Design number 15896

Turnaround star-delta switch, Product range: Control switches, Part group reference: T5B, with black thumb grip and front plate, Contacts: 10, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: D-Y-0-Y-D, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Turnaround star-delta switch Catalog Number 091953 Model Code

T5B-5-15896/E EAN 4015080919537 Product Length/Depth 157 mm Product Height 88 mm Product Width 88 mm Product

Weight 0.86 kg Certifications VDE 0660

IEC/EN 60204

CSA-C22.2 No. 94

UL

UL File No.: E36332
CSA File No.: 012528
IEC/EN 60947
UL Category Control No.: NLRV
UL 60947-4-1
CE
IEC/EN 60947-3
CSA
CSA Class No.: 3211-07
CSA-C22.2 No. 60947-4-1-14 Catalog Notes Rated Short-time Withstand Current (I_{cs}) for a time of 1 second
ETIM for 091953 Low-voltage industrial controls and switchgear (EC001105)
Feature Name
Feature Value
Model (EF000010)
On/Off switch
Number of poles (EF001391)
3
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
No
Rated permanent current I_u (EF001389)
63 A
Rated operation current I_e at AC-3, 400 V (EF001392)
41 A
Rated operation power at AC-3, 400 V (EF001364)
37 kW
Degree of protection (IP), front side (EF003118)
IP65
Degree of protection (NEMA), front side (EF011961)
12
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
0
Suitable for floor mounting (EF007243)
No
Suitable for front mounting (EF007246)
Yes
Suitable for distribution board installation (EF007262)
No
Suitable for intermediate mounting (EF007264)
No
Complete device in housing (EF007317)
No

Hous...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-5-15896/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.