

INDUSTRIAL COMPONENT DATA

T5B-5-15896/X 091952 Y7-91952 EATON ELECTRIC Reversing star-delta switch, 3p, Ie 63A, D-Y-0-Y-D, 45°, mainta..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-5-15896/X



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-5-15896/X
Catalog number	Y7-91952
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-76FA728A80
Generated	2026-08-05

Product Overview

Reversing star-delta switch, 3p, Ie=63A, D-Y-0-Y-D, 45°, maintained, replacement switch

Switch Star-Triangle investment; 3p; 63A; D-Y-0-y-D; 45°; Interlock; replacement switch

Reversing star-delta switches, T5B, 63 A, rear mounting, Basic switch, 5 contact unit(s), Contacts: 10, 60 °, design no. 15896

Turnaround star-delta switch, Product range: Control switches, Part group reference: T5B, Contacts: 10, Design: rear mounting, Basic switch, Switching angle: 60 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Reversing star-delta switches, T5B, 63 A, rear mounting, Basic switch, 5 contact unit(s), Contacts: 10, 60 °, design no.

15896Turnaround star-delta switch, Product range: Control switches, Part group reference: T5B, Contacts: 10, Design: rear mounting, Basic switch, Switching angle: 60 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3Delivery program

Product rangeControl switchesPart group referenceT5BBasic functionReversing star-delta switchesContacts10Designrear mounting

Basic switchSwitching angle60 °Design number15896Front plate no.Motor rating AC-23A, 50 - 60 Hz [P]400 V [P]30

kW Rated uninterrupted current [I_u] 63 A Note on rated uninterrupted current I_u Rated uninterrupted current I_u is specified for max. cross-section. Number of contact units 5 contact unit(s) Technical data
General Standards IEC/EN 60947, VDE 0660, IEC/EN 60204
Switch-disconnector according to IEC/EN 60947-3 Climatic proofing Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Open-25 - +50 °C Ambient temperature Enclosed-25 - +40 °C
Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [U_{imp}] 6000 V AC Mechanical shock resistance 15 g Mounting position As required Contacts Electrical characteristics Rated operational voltage [U_e] 690 V AC
Electrical characteristics Rated uninterrupted current [I_u] 63 A Electr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-5-15896/X with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.