

INDUSTRIAL COMPONENT DATA

T5B-5-33/E 091917 Y7-91917 EATON ELECTRIC Multi-speed switches, Contacts: 9, 63 A, One tapped winding, 2 spe..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-5-33/E



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-5-33/E
Catalog number	Y7-91917
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-1A191759F8
Generated	2026-08-06

Product Overview

Multi-speed switches, Contacts: 9, 63 A, One tapped winding, 2 speeds, front plate: 2-0-1, 60 °, maintained, flush mounting
Switch Multi-speed; 9-pole; 63; 1 winding threading; 2 speeds; rating Plate: 2-0-1; 60 °; Interlock; recessed Mounting
Eaton Moeller® series T5B Multi-speed switches, T5B, 63 A, flush mounting, 5 contact unit(s), Contacts: 9, 60 °, maintained, With 0 (Off) position, 2-0-1, Design number 33

Multi-speed switch, Product range: Control switches, Part group reference: T5B, with black thumb grip and front plate,
Contacts: 9, Degree of Protection: Front IP65, Design: flush mounting, switching function: One tapped winding, 2 speeds,
Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 -
60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660,
IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Multi-speed switch Catalog Number 091917 Model Code T5B-5-33/E EAN 4015080919179 Product Length/Depth 157 mm Product Height 88 mm Product Width 88 mm Product Weight 0.86 kg

Certifications CSA File No.: 012528

UL 60947-4-1

VDE 0660

UL

UL Category Control No.: NLRV

CE

IEC/EN 60947

IEC/EN 60947-3

CSA Class No.: 3211-07

CSA-C22.2 No. 60947-4-1-14

CSA

UL File No.: E36332

CSA-C22.2 No. 94

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (I_{scw}) for a time of 1 second

ETIM for 091917 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Dahlander switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

63 A

Rated operation current I_e at AC-3, 400 V (EF001392)

41 A

Rated operation power at AC-3, 400 V (EF001364)

37 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing materi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-5-33/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.