

INDUSTRIAL COMPONENT DATA

T5B-5-8369/Z 091866 Y7-91866 EATON ELECTRIC

Changeoverswitches, Contacts: 10, 63 A, front plate: 1-2, 90 °,

..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-5-8369/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-5-8369/Z
Catalog number	Y7-91866
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-48EE1CE1B1
Generated	2026-08-06

Product Overview

Changeoverswitches, Contacts: 10, 63 A, front plate: 1-2, 90 °, maintained, rear mounting

Switch Switch 10 poles 63 A Indicator plate: 1-2 90°

Eaton Moeller® series T5B Changeoverswitches, T5B, 63 A, rear mounting, 5 contact unit(s), Contacts: 10, 90 °, maintained, Without 0 (Off) position, 1-2, Design number 8369

Changeover switch, Product range: Control switches, Part group reference: T5B, with black thumb grip and front plate, Contacts: 10, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 90 °, Switching performance: maintained, Without 0 (Off) position, front plate: 1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Changeover switch Catalog Number 091866 Model Code T5B-5-8369/Z EAN 4015080918660 Product Length/Depth 198 mm Product Height 88 mm Product Width 88 mm Product Weight 0.904 kg

Certifications CSA File No.: 012528

CSA Class No.: 3211-05

UL File No.: E36332
IEC/EN 60204
CE
IEC/EN 60947
UL 60947-4-1
UL Category Control No.: NLRV
VDE 0660
CSA
CSA-C22.2 No. 60947-4-1-14
CSA-C22.2 No. 94
IEC/EN 60947-3
UL Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second
ETIM for 091866 Low-voltage industrial controls and switchgear (EC001105)
Feature Name
Feature Value
Model (EF000010)
Reverser
Number of poles (EF001391)
5
With zero (off) position (EF001416)
No
With retraction in 0-position (EF002428)
No
Rated permanent current I_u (EF001389)
63 A
Rated operation current I_e at AC-3, 400 V (EF001392)
41 A
Rated operation power at AC-3, 400 V (EF001364)
22 kW
Degree of protection (IP), front side (EF003118)
IP65
Degree of protection (NEMA), front side (EF011961)
12
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
0
Suitable for floor mounting (EF007243)
Yes
Suitable for front mounting (EF007246)
No
Suitable for distribution board installation (EF007262)
No
Suitable for intermediate mounting (EF007264)
Yes

Complete device in housing (EF007317)

No

Housing material (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-5-8369/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.