

INDUSTRIAL COMPONENT DATA

T5B-6-103/E 091847 Y7-91847 EATON ELECTRIC Multi-speed switches, Contacts: 11, 63 A, One tapped winding, 2 s..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-6-103/E



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-6-103/E
Catalog number	Y7-91847
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-F5D076EFF0
Generated	2026-08-05

Product Overview

Multi-speed switches, Contacts: 11, 63 A, One tapped winding, 2 speeds, front plate: 0-Y-D-2, 60 °, maintained, flush mounting

Switch Multi-speed; 11-pole; 63; 1 winding threading; 2 speeds; rating Plate: 0-y-D-2; 60 °; Interlock; recessed Mounting Eaton Moeller® series T5B Multi-speed switches, T5B, 63 A, flush mounting, 6 contact unit(s), Contacts: 11, 60 °, maintained, With 0 (Off) position, 0-Y-D-2, Design number 103

Multi-speed switch, Product range: Control switches, Part group reference: T5B, with black thumb grip and front plate, Contacts: 11, Degree of Protection: Front IP65, Design: flush mounting, switching function: One tapped winding, 2 speeds, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-Y-D-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, 6 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Multi-speed switch Catalog Number 091847 Model Code T5B-6-103/E EAN 4015080918479 Product Length/Depth 174 mm Product Height 88 mm Product Width 88 mm Product Weight 0.995 kg Certifications VDE 0660

IEC/EN 60204

IEC/EN 60947

CSA
UL 60947-4-1
CSA-C22.2 No. 60947-4-1-14
CSA-C22.2 No. 94
CSA Class No.: 3211-07
UL Category Control No.: NLRV
UL File No.: E36332
CE
CSA File No.: 012528
IEC/EN 60947-3
UL Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second
ETIM for 091847 Low-voltage industrial controls and switchgear (EC001105)
Feature Name
Feature Value
Model (EF000010)
Dahlander switch
Number of poles (EF001391)
3
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
No
Rated permanent current I_u (EF001389)
63 A
Rated operation current I_e at AC-3, 400 V (EF001392)
41 A
Rated operation power at AC-3, 400 V (EF001364)
37 kW
Degree of protection (IP), front side (EF003118)
IP65
Degree of protection (NEMA), front side (EF011961)
12
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
0
Suitable for floor mounting (EF007243)
No
Suitable for front mounting (EF007246)
Yes
Suitable for distribution board installation (EF007262)
No
Suitable for intermediate mounting (EF007264)
No
Complete device in housing (EF007317)

No
Housing mate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-6-103/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.