

INDUSTRIAL COMPONENT DATA

T5B-6-15168/EA/SVB-SW 091820 Y7-91820 EATON ELECTRIC

Main switch, 9-pole + 2 N/O + 1 N/C, 63 A, STOP functio..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-6-15168/EA/SVB-SW



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-6-15168/EA/SVB-SW
Catalog number	Y7-91820
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-5B331E9A31
Generated	2026-08-05

Product Overview

Main switch, 9-pole + 2 N/O + 1 N/C, 63 A, STOP function, 90 °, flush mounting

General switch; 9-pole + 2 NO + 1 NC; 63; Lever Black; Lockable in position (OFF); 90 °; Mounting

Eaton Moeller® series T5B Main switch, T5B, 63 A, flush mounting, 6 contact unit(s), 9-pole, 2 N/O, 1 N/C, STOP function, With black rotary handle and locking ring

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T5B, Stop Function: STOP function, With black rotary handle and locking ring, 9-pole, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, 6 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Main switch Catalog Number 091820 Model Code T5B-6-15168/EA/SVB-SW

EAN 4015080918202 Product Length/Depth 206 mm Product Height 88 mm Product Width 88 mm Product Weight 1.245 kg

Certifications CSA-C22.2 No. 60947-4-1-14

UL Category Control No.: NLRV

CSA

UL 60947-4-1

CSA Class No.: 3211-05

UL File No.: E36332
CSA File No.: 012528
IEC/EN 60947-3
CSA-C22.2 No. 94
CE
IEC/EN 60947
UL
IEC/EN 60204
VDE 0660 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second
ETIM for 091820 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as main switch (EF006981)
Yes
Version as maintenance-/service switch (EF006986)
Yes
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
No
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Rated operating voltage (EF001435)
690 V
Rated permanent current I_u (EF001389)
63 A
Rated permanent current at AC-21, 400 V (EF009165)
63 A
Rated operation power at AC-3, 400 V (EF001364)
22 kW
Rated short-time withstand current I_{cw} (EF007050)
1.3 kA
Rated operation power at AC-23, 400 V (EF007027)
30 kW
Switching power at 400 V (EF009166)
30 kW
Conditioned rated short-circuit current I_q (EF001444)
2 kA
Number of poles (EF001391)
9
Number of auxiliary contacts as normally closed contact (EF001377)
1
Number of auxiliary contacts as normally open contact (EF001376)
2
Number of auxiliary cont...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-6-15168/EA/SVB-SW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.