

INDUSTRIAL COMPONENT DATA

T5B-6-15893/E 091791 Y7-91791 EATON ELECTRIC Star-delta switches, Contacts: 11, 63 A, front plate: B 0-Y-D, ..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-6-15893/E



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-6-15893/E
Catalog number	Y7-91791
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-3501EE2BD9
Generated	2026-08-06

Product Overview

Star-delta switches, Contacts: 11, 63 A, front plate: B>0-Y-D, 60 °, momentary/maintained, flush mounting, SOND 28 Switch Star-Triangle; 11-pole; 63; rating Plate: B>0-And-D; 60 °; - Return/Latching; flush Mount; SOND 28 Eaton Moeller® series T5B Star-delta switches, T5B, 63 A, flush mounting, 6 contact unit(s), Contacts: 11, 60 °, momentary/maintained, With 0 (Off) position, With spring-return to 0, B>0-Y-D, SOND 28, Design number 15893 Star-delta switch, Product range: Control switches, Part group reference: T5B, with black thumb grip and front plate, Notes: SOND 28, Contacts: 11, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 60 °, Switching performance: momentary/maintained, With 0 (Off) position, With spring-return to 0, front plate: B>0-Y-D, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, 6 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Star-delta switch Catalog Number 091791 Model Code T5B-6-15893/E EAN 4015080917915 Product Length/Depth 174 mm Product Height 88 mm Product Width 88 mm Product Weight 0.995 kg Certifications IEC/EN 60204

UL

CE

CSA File No.: 012528

CSA

CSA-C22.2 No. 94

UL Category Control No.: NLRV

CSA Class No.: 3211-07

VDE 0660

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947

IEC/EN 60947-3

UL 60947-4-1

UL File No.: E36332 Catalog Notes Rated Short-time Withstand Current (I_{cs}) for a time of 1 second

ETIM for 091791 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Star-delta switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

Yes

Rated permanent current I_u (EF001389)

63 A

Rated operation current I_e at AC-3, 400 V (EF001392)

41 A

Rated operation power at AC-3, 400 V (EF001364)

37 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-6-15893/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.