

INDUSTRIAL COMPONENT DATA

T5B-6-15898/Z 091786 Y7-91786 EATON ELECTRIC Reversing star-delta switches, Contacts: 11, 63 A, front plate:..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-6-15898/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-6-15898/Z
Catalog number	Y7-91786
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-75728C7C06
Generated	2026-08-06

Product Overview

Reversing star-delta switches, Contacts: 11, 63 A, front plate: D-Y-0-Y-D, 60 °, maintained, rear mounting, SOND 30 Switch Star-delta with reversing; 11-pole; 63; rating Plate: D-y-0-y-D; 60 °; Interlocking; Installation bottom panel; SOND 30 Eaton Moeller® series T5B Reversing star-delta switches, T5B, 63 A, rear mounting, 6 contact unit(s), Contacts: 11, 60 °, maintained, With 0 (Off) position, D-Y-0-Y-D, SOND 30, Design number 15898

Turnaround star-delta switch, Product range: Control switches, Part group reference: T5B, with black thumb grip and front plate, Notes: SOND 30, Contacts: 11, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: D-Y-0-Y-D, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: I_u = 63 A, 6 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Turnaround star-delta switch Catalog Number 091786 Model Code T5B-6-15898/Z EAN 4015080917861 Product Length/Depth 215 mm Product Height 88 mm Product Width 88 mm Product Weight 1.039 kg Certifications CSA Class No.: 3211-05
UL 60947-4-1
UL
CSA

CE
VDE 0660
IEC/EN 60947-3
UL Category Control No.: NLRV
IEC/EN 60204
CSA-C22.2 No. 94
CSA File No.: 012528
IEC/EN 60947
UL File No.: E36332
CSA-C22.2 No. 60947-4-1-14 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 091786 Low-voltage industrial controls and switchgear (EC001105)
Feature Name
Feature Value
Model (EF000010)
Turnaround star-delta switch
Number of poles (EF001391)
3
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
No
Rated permanent current Iu (EF001389)
63 A
Rated operation current Ie at AC-3, 400 V (EF001392)
41 A
Rated operation power at AC-3, 400 V (EF001364)
37 kW
Degree of protection (IP), front side (EF003118)
IP65
Degree of protection (NEMA), front side (EF011961)
12
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
0
Suitable for floor mounting (EF007243)
Yes
Suitable for front mounting (EF007246)
No
Suitable for distribution board installation (EF007262)
No
Suitable for intermediate mounting (EF007264)
Yes
Complete device in housing (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-6-15898/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.