

INDUSTRIAL COMPONENT DATA

T5B-7-8363/E 091422 Y7-91422 EATON ELECTRIC

Changeoverswitches, Contacts: 14, 63 A, front plate: 1-0-2, 60 °

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-7-8363/E



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-7-8363/E
Catalog number	Y7-91422
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-D0CAC84ECC
Generated	2026-08-04

Product Overview

Changeoverswitches, Contacts: 14, 63 A, front plate: 1-0-2, 60 °, maintained, flush mounting

Switch Switch 14 poles 63 A Indicator plate: 1-0-2 60°

Eaton Moeller® series T5B Changeoverswitches, T5B, 63 A, flush mounting, 7 contact unit(s), Contacts: 14, 60 °, maintained, With 0 (Off) position, 1-0-2, Design number 8363

Changeover switch, Product range: Control switches, Part group reference: T5B, with black thumb grip and front plate, Contacts: 14, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 1-0-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, 7 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5B Changeover switch Catalog Number 091422 Model Code T5B-7-8363/E EAN 4015080914228 Product Length/Depth 190 mm Product Height 88 mm Product Width 88 mm Product Weight 1.13 kg

Certifications UL 60947-4-1

UL

UL Category Control No.: NLRV

IEC/EN 60947-3

CSA File No.: 012528

CSA-C22.2 No. 94

CE

IEC/EN 60947

UL File No.: E36332

IEC/EN 60204

CSA-C22.2 No. 60947-4-1-14

CSA

VDE 0660

CSA Class No.: 3211-07 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 091422 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reverser

Number of poles (EF001391)

7

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

63 A

Rated operation current Ie at AC-3, 400 V (EF001392)

41 A

Rated operation power at AC-3, 400 V (EF001364)

22 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material (EF0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-7-8363/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.