

## INDUSTRIAL COMPONENT DATA

# TBC4 EATON ELECTRIC Fuse-link, low voltage, 4 A, AC 660 V, DC 460 V, BS88, 27 x 129 mm, gL/gG, BS

Brand: EATON - MOELLER | Manufacturer Part Number: TBC4



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | TBC4            |
| Catalog number  | 10000           |
| Category        | HRC fuse        |
| Minimum order   | 20 Pcs          |
| Document ID     | EO-617D4CFA70   |
| Generated       | 2026-08-06      |

## Product Overview

4A 660V AC / 460V DC INDUSTRIAL FUSE

Fuse-link, low voltage, 4 A, AC 660 V, DC 460 V, BS88, 27 x 129 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 4 A, AC 660 V, DC 460 V, BS88, 27 x 129 mm, gL/gG, BS, centre-bolted tags, general industrial applications, BS88, IEC 60269, Breaking Capacity 80 kA, Optional accessories fuse-holder RS200

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Bussmann Series Low Voltage fuses and accessories

## Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number TBC4 EAN 5027590513142

Product Length/Depth 27 mm Product Height 27 mm Product Width 129 mm Product Weight 91.75 g Compliances CE Marked

RoHS Compliant Certifications BS88

IEC 60269

EAC Electrical data

Amperage Rating 4 A Voltage rating 660 V Voltage type AC/DC Breaking capacity 80 kA Class Class gG/gL Product specifications

Fuse type TBC Fitted with: Centre bolted tags Construction BS88

ETIM for TBC4 Circuit breakers and fuses (EC004556)

Feature Name

**Feature Value**

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

660 V

Rated voltage DC (EF012281)

460 V

Rated current (EF000227)

4 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Mounting holes (EF021553)

M8

Centre-to-centre distance of connections (EF021151)

111 mm

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send EATON - MOELLER / TBC4 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.