

INDUSTRIAL COMPONENT DATA

TCP40A TCP40 EATON ELECTRIC Fuse-link, low voltage, 40 A, AC 660 V, DC 460 V, BS88/A4, 26 x 110 mm, gL/gG, BS

Brand: EATON - MOELLER | Manufacturer Part Number: TCP40A



Manufacturer	EATON - MOELLER
MPN / Reference	TCP40A
Catalog number	TCP40
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-2FDB2EC97E
Generated	2026-08-06

Product Overview

40A 660V AC / 460V DC INDUSTRIAL FUSE

Fuse-link, low voltage, 40 A, AC 660 V, DC 460 V, BS88/A4, 23 x 109 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 40 A, AC 660 V, DC 460 V, BS88/A4, 23 x 109 mm, gL/gG, BS, offset bolted tags (slotted), general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder RS100

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number TCP40A EAN 5027590513432

UPC 051712485159 Product Length/Depth 109 mm Product Height 23 mm Product Width 23 mm Product Weight 83.4 g

Compliances CE Marked

RoHS Compliant Certifications IEC Rated

BS88

IEC 60269

EAC Electrical data

Amperage Rating 40 A Voltage rating 660 V Voltage type AC/DC Breaking capacity 80 kA Class Class gG/gL Compatible fuse holder

Suitable for RS100 Red spot fuse holder Product specifications

Fuse type TCP Fitted with: Offset bolted tags Construction BS88/A4

ETIM for TCP40A Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

A4

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

660 V

Rated voltage DC (EF012281)

460 V

Rated current (EF000227)

40 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Mounting holes (EF021553)

M8

Centre-to-centre distance of connections (EF021151)

93.7 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TCP40A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.