

INDUSTRIAL COMPONENT DATA

TDC 120 20A BUSS 100 BAG BK/C1520 BK-C1520 EATON ELECTRIC Fuse-link, high speed, 1700 A, AC 1250 V, size 4, ..

Brand: EATON - MOELLER | Manufacturer Part Number: TDC 120 20A BUSS 100 BAG



Manufacturer	EATON - MOELLER
MPN / Reference	TDC 120 20A BUSS 100 BAG
Catalog number	BK-C1520
Category	Cylindrical fuse
Minimum order	1 Pcs
Document ID	EO-6C029249DB
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 1700 A, AC 1250 V, size 4, 100 x 120 x 106 mm, aR, IEC, single indicator

fuse cartridge, BT, 20 A, AC 240 V, BS1361, 11 x 26 mm, BS

BK/C1520 - Fuse-link, low voltage, 20 A, AC 240 V, BS1361, 11 x 26 mm, BS

Fuse, Fuse-link, low voltage, 20 A, AC 240 V, BS1361, 11 x 26 mm, BS, cylindrical, 100 bulk pack, consumer unit, BS1361, Breaking Capacity 16.5 kA, Ceramic body

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann EWS fuses

Additional Product Information

Fuse-link, low voltage, 20 A, AC 240 V, BS1361, 11 x 26 mm, BS Fuse, Fuse-link, low voltage, 20 A, AC 240 V, BS1361, 11 x 26 mm, BS, cylindrical, 100 bulk pack, consumer unit, BS1361, Breaking Capacity 16.5 kA, Ceramic body Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 20 A Rated voltage AC 240 V Construction size BS1361 Size 11 x 26 mm Description 100 bulk pack Breaking Capacity 16.5 kA usable for size/applications consumer unit Standard/Approval BS Shape cylindrical Material Ceramic body Standards/Regulations BS1361 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) () [AFZ797013]) Size Other Rated voltage 240 - 240 V Rated voltage Other Voltage type AC Utilization category gL/gG (cable protection/equipment protection) Rated operating frequency 45 - 62 Hz Nominal current 20 A With striker No Release

characteristic Other Breaking capacity 16.5 kA
ETIM for BK/C1520 Circuit breakers and fuses (EC002704)
Feature Name
Feature Value
Size (EF000088)
11x26 mm
Voltage type (EF000187)
AC
Rated current (EF000227)
20 A
Utilization category according to IEC 60269 (EF002572)
gG (cable protection/equipment protection)
Release characteristic (EF000889)
Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TDC 120 20A BUSS 100 BAG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.