

INDUSTRIAL COMPONENT DATA

BPZ-KB-8/125 289968 Y7-289968 EATON ELECTRIC Terminal block 4 poles, 125A

Brand: EATON - MOELLER | Manufacturer Part Number: BPZ-KB-8/125



Manufacturer	EATON - MOELLER
MPN / Reference	BPZ-KB-8/125
Catalog number	Y7-289968
Category	Distributor assembly terminal blocks
Minimum order	1 Pcs
Document ID	EO-EDEFB2147A
Generated	2026-08-05

Product Overview

Terminal block 4 poles, 125A

BPZ-KB-8/125

Eaton xEnergy Basic LV systems Low voltage switchgear. Terminal block, 4 poles, 125A

4-pole terminal block, BPZ-KB, rated operational current 125 A, mounting on DIN-rail and mounting plate, max. operational voltage 1000 V AC , 1500 VDC. Equipment supplied: 1 4 pole terminal block

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Enclosures

Additional Product Information

General specifications

Product Name Eaton xEnergy Basic other accessory Catalog Number 289968 Model Code BPZ-KB-8/125 EAN

4015082899684 Product Length/Depth 49 mm Product Height 74.5 mm Product Width 98 mm Product Weight 0.32 kg

Compliances RoHS conform Certifications IEC 60 947 -7 -1 Delivery program

Amperage rating 125 A Number of poles Four-pole Technical data - electrical

Voltage rating at AC Cu (IEC) - max 690 VAC Voltage rating at DC Cu (IEC) - max 690 VDC Rated peak withstand current

24 kA Rated operation current (Ie) Cu (IEC) 125 A Rated short-time withstand current (Icw) 4.2 kA Technical data - mechanical

Mounting method Surface mounting

Flush mounting

Floor standing distribution board Mounting position Universal Number of clamp positions per pole 18 Number of clamping

units per pole 9 Terminal capacity (single/multi-wire) 6 mm² - 35 mm² (incoming)

1.5 mm² - 10 mm² (N outgoing)

4 mm² - 16 mm² (L1-L3 outgoing)

4 mm² - 16 mm² (outgoing)

1.5 mm² - 6 mm² (L1-L3 outgoing)

4 mm² - 16 mm² (outgoing, fine wire (with sleeve) N)

1.5 mm² - 6 mm² (outgoing, fine wire (with sleeve) L1 - L3)

6 mm² - 25 mm² (incoming, fine wire (with sleeve))

4 mm² - 16 mm² (N outgoing)

1.5 mm² - 6 mm² (outgoing)

4 mm² - 10 mm² (outgoing, fine wire (with sleeve) N)

4 mm² - 10 mm² (outgoing, fine wire (with sleeve) L1 - L3) Conductor cross section (flexible, fine-strand) with cable end sleeve - min 1.5 mm² Conductor cross section (flexible, fine-strand) with cable end sleeve - max 35 mm² Conductor....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPZ-KB-8/125 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.