

INDUSTRIAL COMPONENT DATA

BBA-TP3/16 107205 Y7-107205 EATON ELECTRIC Terminal module, 1.5-16mm², 3p, 20mm

Brand: EATON - MOELLER | Manufacturer Part Number: BBA-TP3/16



Manufacturer	EATON - MOELLER
MPN / Reference	BBA-TP3/16
Catalog number	Y7-107205
Category	Busbar terminal
Minimum order	1 Pcs
Document ID	EO-60C3B11499
Generated	2026-08-02

Product Overview

Terminal module, 1.5-16mm², 3p, 20mm

BBA-TP3/16

Eaton xEffect SASy 60i Enclosures Switch- & Controlgear Enclosure. Terminal module, 1.5-16mm², 3p, 20mm
Connection terminal board, 60 mm system, poles=3, spring-loaded terminal, terminal capacity=1.5 up to 16mm² or
AWG16-AWG6, I_e=80A, width=20mm, can be used for rail 12x5/10 to 30x5/10 and double T profile, silicon free, chlorine
free, self-extinguishing to UL 94, track resistance CTI 200, temperature resistant to 120 °C, fixing directly on busbars

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton xEffect SASy 60i terminal plate Catalog Number 107205 Model Code BBA-TP3/16 EAN
4015081069682 Product Length/Depth 90 mm Product Height 200 mm Product Width 20 mm Product Weight 0.18 kg
Compliances UL CSA09 (refer to approbation report)
RoHS conform Certifications UL (File No. E300273)
UL508A
IEC 60439-1
CE marking
CSA-C22.2 No. 14
North America (UL listed, CSA certified)

UL (Category Control Number NMTR, NMTR7)

CSA (Class No. 3211-37)

CSA (File No. 236217) Catalog Notes 12 x 5/10, 15 x 5/10, 20 x 5/10, 25 x 5/10, 30 x 5/10 Delivery program

Type Technical data - electrical

Voltage rating (UL CSA 13) Max. 600 V AC Rated operation current (Ie) 80 A Rated operational current 80 A Rated operational current (Ie) - max 80 A Creepage resistance CTI 200 Technical data - mechanical

Material Silicon free, chlorine free Degree of protection UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking

Feeder circuits Busbar thickness - min 5 mm Busbar thickness - max 10 mm Busbar width - min 12 mm Busbar width - max 30 mm Terminal capacity (conductor) AWG 16 - AWG 6

1.5 mm² - 16 mm² Conductor cross section - max 16 mm² Width clamp 20 mm Design verification as per IEC/EN 61439 - technical data

Temperature resistance Temperature resistant to 120 °C Additional information

Features Self-extinguishing acc. UL 94 Functions Clamp plate

Current limiting circuit breaker, refer to approbation report

Connections Suitable for Flat rail

Round conductor connection

Three...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BBA-TP3/16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.