

INDUSTRIAL COMPONENT DATA

BBA-TP3/50 107183 Y7-107183 EATON ELECTRIC Terminal plate, 6-50mm², 54 mm

Brand: EATON - MOELLER | Manufacturer Part Number: BBA-TP3/50



Manufacturer	EATON - MOELLER
MPN / Reference	BBA-TP3/50
Catalog number	Y7-107183
Category	Busbar terminal
Minimum order	1 Pcs
Document ID	EO-3D276BAE55
Generated	2026-08-03

Product Overview

Terminal plate, 6-50mm², 54 mm

BBA-TP3/50

Eaton xEffect SASY 60i Enclosures Switch- & Controlgear Enclosure. Terminal plate, 6-50mm², 54 mm
Connection terminal board, 60 mm system, poles=3, screw terminals, terminal capacity=6 up to 50mm² or AWG10-AWG2 or 6x9x0.8, Ie=300A, width=54mm, can be used for rail 12x5/10 to 30x5/10 and double T profile, silicon free, chlorine free, self-extinguishing to UL 94, track resistance CTI 200, temperature resistant to 120 °C, the terminal can be removed for the connection of uncut conductors, termination space WxH = 15x10 mm, passing through is not possible

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers PKZ**

Additional Product Information

General specifications

Product Name Eaton xEffect SASY 60i terminal plate Catalog Number 107183 Model Code BBA-TP3/50 EAN 4015081069460 Product Length/Depth 95 mm Product Height 210 mm Product Width 115 mm Product Weight 0.435 kg
Compliances UL CSA09 (refer to approbation report)
RoHS conform Certifications CSA-C22.2 No. 14
IEC 60439-1
UL508A
UL (Category Control Number NMTR, NMTR7)
CSA (File No. 236217)

North America (UL listed, CSA certified)

CSA (Class No. 3211-37)

UL (File No. E300273)

CE marking Delivery program

Type Technical data - electrical

Voltage rating (UL CSA 13) Max. 600 V AC Rated operation current (Ie) 300 A Rated operational current 300 A Rated operational current (Ie) - max 300 A Creepage resistance CTI 200 Technical data - mechanical

Material Silicon free, chlorine free Degree of protection Feeder circuits

UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking Busbar thickness - min 5 mm Busbar thickness - max 10 mm

Busbar width - min 12 mm Busbar width - max 30 mm Terminal contact area 10 mm x 15 mm Terminal capacity (conductor)

AWG 10 - AWG 2/0

9 mm x 0.8 mm (6x)

6 mm² - 50 mm² Conductor cross section - max 50 mm² Width clamp 54 mm Design verification as per IEC/EN 61439 - technical data

Temperature resistance Temperature resistant to 120 °C Additional information

Features Self-extinguishing acc. UL 94 Functions Connections

Clamp plate

Current limiting circuit breaker, refer to approbation report Special features The terminal can be removed for the connection...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BBA-TP3/50 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.