


INDUSTRIAL COMPONENT DATA

B3.2/2-PKZ0 063963 Y7-63963 EATON ELECTRIC Three-phase commoning link, for 2 PKZ0, +auxiliary contact, +volt..

Brand: EATON - MOELLER | Manufacturer Part Number: B3.2/2-PKZ0



Manufacturer	EATON - MOELLER
MPN / Reference	B3.2/2-PKZ0
Catalog number	Y7-63963
Category	Phase busbar
Minimum order	10 Pcs
Document ID	EO-4800437E4B
Generated	2026-08-05

Product Overview

Three-phase commoning link, for 2 PKZ0, +auxiliary contact, +voltage release

Three-phase connection comb For 2 PKZ0 + auxiliary contact + coil

Eaton Moeller® series B3 Three-phase busbar link, Circuit-breaker: 2, 108 mm, For PKZM0-... or PKE12, PKE32 without side mounted auxiliary contacts or voltage releases

Three-phase busbar link 3 poles for feeder unit of 2 PKZM0-... with auxiliary contact or trip indicator built onto the right side or a voltage release built onto the left side, length 108mm protective against direct contact., Ue = 690 V, Iu = 63 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers PKZ**

Additional Product Information

General specifications

Product Name Eaton Moeller® series B3 Accessory Three-phase busbar link Catalog Number 063963 Model Code B3.2/2-PKZ0 EAN 4015080639633 Product Length/Depth 109 mm Product Height 34 mm Product Width 11 mm Product Weight 0.039 kg Certifications CSA-C22.2 No. 14

UL File No.: E36332

IEC/EN 60947-4-1

UL Category Control No.: NLRV

UL

CSA File No.: 98494

CE

UL 508

CSA

CSA Class No.: 3211-06 Catalog Notes For parallel power feed to several motor-protective circuit-breakers on terminals 1, 3, 5 Features & Functions

Color Black Electric connection type Fork Features Insulated Functions Can be extended by rotating installation Number of phases 3 Number of poles Three-pole General

Mounting width 45 + 18 mm Overvoltage category III Pollution degree 3 Product category Accessories Rated impulse withstand voltage (Uimp) 6000 V AC Suitable for 2 Circuit-breakers Used with PKZ0

PKE12

PKE32 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Electrical rating

Rated operational voltage (Ue) - max 690 V Rated operational voltage (Ue) at AC - max 690 V Rated uninterrupted current (Iu) 63 A Short-circuit rating

Rated conditional short-circuit current (Iq) 0 kA Rated short-time withstand current (Icw) 0 kA Design verification

Equipment heat dissipation, current-dependent Pvid 3.6 W Heat dissipation capacity Pdis 0 W Heat dissipation per pole, current-dependent Pvid 1.2 W Rated operational current for specifie...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / B3.2/2-PKZ0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.