

INDUSTRIAL COMPONENT DATA

B3.0/2-PKZ4 220220 Y7-220220 EATON ELECTRIC

Three-phase commoning link, for 2 PKZ4

Brand: EATON - MOELLER | Manufacturer Part Number: B3.0/2-PKZ4



Manufacturer	EATON - MOELLER
MPN / Reference	B3.0/2-PKZ4
Catalog number	Y7-220220
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-15A15B64CB
Generated	2026-08-02

Product Overview

Three-phase commoning link, for 2 PKZ4

B3.0/2-PKZ4

Eaton Moeller® series B3 Three-phase busbar link, Circuit-breaker: 2, 110 mm

Three-phase busbar link 3 poles for feeder unit of 2 PKZM4-... without auxiliary contact or voltage release built on laterally, can be extended by rotating installation, length 110mm protective against direct contact., Ue = 690 V, Iu = 128 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton Moeller® series B3 Accessory Three-phase busbar link Catalog Number 220220 Model Code

B3.0/2-PKZ4 EAN 4015082202200 Product Length/Depth 98 mm Product Height 36 mm Product Width 33 mm Product

Weight 0.128 kg Certifications CSA Class No.: 3211-06

UL

CSA File No.: 165628

CSA-C22.2 No. 14

CSA

UL Category Control No.: NLRV

UL File No.: E36332

CE

IEC/EN 60947-4-1

UL 508 Features & Functions

Color Black Electric connection type Pin Features Insulated Number of phases 3 Number of poles Three-pole General Mounting width 55 mm Overvoltage category III Pollution degree 3 Product category Accessories Rated impulse withstand voltage (Uimp) 6000 V AC Suitable for 2 Circuit-breakers Climatic environmental conditions Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Electrical rating Rated operational voltage (Ue) - max 690 V Rated operational voltage (Ue) at AC - max 690 V Rated uninterrupted current (Iu) 128 A Short-circuit rating Rated conditional short-circuit current (Iq) 0 kA Rated short-time withstand current (Icw) 0 kA Design verification Equipment heat dissipation, current-dependent Pvid 5.7 W Heat dissipation capacity Pdis 0 W Heat dissipation per pole, current-dependent Pvid 1.9 W Rated operational current for specified heat dissipation (In) 128 A Static heat dissipation, non-current-dependent Pvs 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of therma...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / B3.0/2-PKZ4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.