


INDUSTRIAL COMPONENT DATA

B3.1/4-PKZ0 044947 Y7-44947 EATON ELECTRIC Three-phase commoning link, for 4 PKZ0, +auxiliary contact

Brand: EATON - MOELLER | Manufacturer Part Number: B3.1/4-PKZ0



Manufacturer	EATON - MOELLER
MPN / Reference	B3.1/4-PKZ0
Catalog number	Y7-44947
Category	Phase busbar
Minimum order	1 Pcs
Document ID	EO-0F2A2B8FCF
Generated	2026-08-06

Product Overview

Three-phase commoning link, for 4 PKZ0, +auxiliary contact

Three-phase connection comb. For 4 PKZ0. + Auxiliary contact

Eaton Moeller® series B3 Three-phase busbar link, Circuit-breaker: 4, 207 mm, For PKZM0-... or PKE12, PKE32 without side mounted auxiliary contacts or voltage releases

Three-phase busbar link 3 poles for feeder unit of 4 PKZM0-... with auxiliary contact or trip indicator built onto the right side, length 207mm protective against direct contact., Ue = 690 V, Iu = 63 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers PKZ**

Additional Product Information

General specifications

Product Name Eaton Moeller® series B3 Accessory Three-phase busbar link Catalog Number 044947 Model Code

B3.1/4-PKZ0 EAN 4015080449478 Product Length/Depth 209 mm Product Height 34 mm Product Width 11 mm Product

Weight 0.09 kg Certifications UL 508

CE

CSA

CSA File No.: 98494

UL File No.: E36332

CSA Class No.: 3211-06

UL Category Control No.: NLRV

UL
CSA-C22.2 No. 14
IEC/EN 60947-4-1 Features & Functions
Color Black Electric connection type Fork Features Insulated Functions Can be extended by rotating installation Number of phases 3 Number of poles Three-pole General
Mounting width 45 + 9 mm Overvoltage category III Pollution degree 3 Product category Accessories Rated impulse withstand voltage (Uimp) 6000 V AC Suitable for 4 Circuit-breakers Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Electrical rating
Rated operational voltage (Ue) - max 690 V Rated operational voltage (Ue) at AC - max 690 V Rated uninterrupted current (Iu) 63 A Short-circuit rating
Rated conditional short-circuit current (Iq) 0 kA Rated short-time withstand current (Icw) 0 kA Design verification
Equipment heat dissipation, current-dependent Pvid 6.9 W Heat dissipation capacity Pdis 0 W Heat dissipation per pole, current-dependent Pvid 2.3 W Rated operational current for specified heat dissipation (In) 63 A Static heat dissipation, non-current-dependent Pvs 0 W 10.2.2 Corrosion resistance Meets the product sta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / B3.1/4-PKZ0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.