

## INDUSTRIAL COMPONENT DATA

**DTZ25(\*/\*)\* 914816 Y7-914816 EATON ELECTRIC Three-phase control/isolation/safety transformer, 2kVA, non-stan..**

Brand: EATON - MOELLER | Manufacturer Part Number: DTZ25(\*/\*)\*



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | EATON - MOELLER                 |
| MPN / Reference | DTZ25(*/*)*                     |
| Catalog number  | Y7-914816                       |
| Category        | Three-phase control transformer |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-2E5D3F3E29                   |
| Generated       | 2026-08-03                      |

**Product Overview**

Three-phase control/isolation/safety transformer, 2kVA, non-standard voltage

DTZ25(\*/\*)\*

Three-phase control isolating safety transformer, 25 kVA, Rated input voltage 50 - 950  $\pm$  5 % V, Rated output voltage 18.5 - 1000 V

Three-phase control transformer performed according to VDE 0550, VDE 0550 part1, IEC/EN 61558-2-2, VDE0570 part 2-2 as safety transformer VDE 0570 part 2-6 and as isolating transformer VDE 0570 part 2-4, UL 506, CSA 22.2 No.66, OVE.

Rated input voltage selectable of 50-950V  $\pm$  5%, rated output voltage can be selected from 18.5 - 1000 rated power 25 kVA

(\*/\*) = wildcard for rated input voltage / rated output voltage

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

|              |                                |
|--------------|--------------------------------|
| Catalog path | EATON - MOELLER > Transformers |
|--------------|--------------------------------|

**Additional Product Information**

Three-phase control isolating safety transformer, 25 kVA, Rated input voltage 50 - 950  $\pm$  5 % V, Rated output voltage 18.5 - 1000 V  
Three-phase control transformer performed according to VDE 0550, VDE 0550 part1, IEC/EN 61558-2-2, VDE0570 part 2-2 as safety transformer VDE 0570 part 2-6 and as isolating transformer VDE 0570 part 2-4, UL 506, CSA 22.2 No.66, OVE. Rated input voltage selectable of 50-950V  $\pm$  5%, rated output voltage can be selected from 18.5 - 1000 rated power 25 kVA (\*/\*) = wildcard for rated input voltage / rated output voltage

General specifications  
Product name Eaton Moeller® series DTZ Control transformer  
Part no. DTZ25(\*/\*)\*  
Product

Length/Depth 281 millimetre  
Product height 434 millimetre  
Product width 450 millimetre  
Product weight 160

kilogram  
Certifications UL Category Control No.: XPTQ2, XPTQ8

IEC/EN 61558-2-2

CEProduct TradenameDTZProduct TypeControl transformerProduct Sub TypeNoneGeneral informationAmbient operating temperature - min-25 °CAmbient operating temperature - max40 °CDegree of protectionIP00

NEMA OtherProduct categoryThree-phase DTZ control transformersSuitable forBranch circuits, (UL/CSA)Electrical ratingRated power25000 V·ARelative short-circuit voltage3 %Short-time rating62 kV·AVoltage rating - max600 VDesign verificationEquipment heat dissipation, current-dependent Pvid0 WHeat dissipation capacity Pdisso WHeat dissipation per pole, current-dependent Pvid0 WRated operational current for specified heat dissipation (In)0 AStatic heat dissipation, non-cu...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DTZ25(\*/\*)\* with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.