

INDUSTRIAL COMPONENT DATA

SVB-P3 052999 Y7-52999 EATON ELECTRIC Thumb-grip, red, lockable with padlock, for P3

Brand: EATON - MOELLER | Manufacturer Part Number: SVB-P3



Manufacturer	EATON - MOELLER
MPN / Reference	SVB-P3
Catalog number	Y7-52999
Category	Handle for power circuit breaker
Minimum order	1 Pcs
Document ID	EO-4F3FB78BC3
Generated	2026-08-03

Product Overview

Thumb-grip, red, lockable with padlock, for P3

Padlock lockable lever Red/Yellow for P3

Eaton Moeller® series SVB Thumb-grip, red, lockable with padlock, for P3

Handle, Basic function: Assembly kits, Function: main switch assembly kits, only for main switch, With padlocking feature, for interlocking the 0 position, Lockable with a maximum of 3 padlocks, For use with: T5B-.../E, .../Z, .../I4, T5-.../E, .../Z, .../I5, P3-63/E, .../Z, .../I4, P3-100/E, .../Z, .../I5, For use with: T5 and T5B up to max. 8 contact units, red/yellow, Type With red rotary handle and yellow locking ring, Emergency switching off/emergency stop: as emergency switching off/emergency stop function, Switching angle: 90 °

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series SVB Accessory Handle Catalog Number 052999 Model Code SVB-P3 EAN 4015080529996 Product Length/Depth 100 mm Product Height 65 mm Product Width 65 mm Product Weight 0.12 kg

Certifications UL/CSA certification not required Features & Functions

Color Red Features Lockable Fitted with: Padlocking feature Functions Emergency stop function

Emergency switching off function Locking facility Lockable with a maximum of 3 padlocks Locking mechanism Lockable in the 0 (Off) position (interlock) General

Ambient operating temperature - min -25 °C Ambient operating temperature - max 50 °C Degree of protection NEMA Other

Suitable for Switch disconnecter

Only for main switch Switching angle 90 ° Type Used with T5-.../E, .../Z, .../I5

T5B-.../E, .../Z, .../I4 Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SVB-P3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.