

INDUSTRIAL COMPONENT DATA

400A 240V THYRISTOR FUSE (1) 400LMMT EATON ELECTRIC Fuse, Air fuse-link, medium voltage, 10 A, AC 12 kV, 51 ..

Brand: EATON - MOELLER | Manufacturer Part Number: 400A 240V THYRISTOR FUSE (1)



Manufacturer	EATON - MOELLER
MPN / Reference	400A 240V THYRISTOR FUSE (1)
Catalog number	400LMMT
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-3DD56DFD65
Generated	2026-08-06

Product Overview

Fuse, Air fuse-link, medium voltage, 10 A, AC 12 kV, 51 x 359 mm, back-up, BS, with striker, style 36 tags

400A 240V THYRISTOR FUSE (1)

400A 240V Fuse-link, high speed, 400 A, AC 240 V, DC 150 V, 200 kA, BS88, 83 x 84 mm, aR, BS

Fuse, Fuse-link, high speed, 400 A, AC 240 V, DC 150 V, BS88, 83 x 84 mm, aR, BS, offset bolted tags, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-0111

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

Fuse-link, high speed, 400 A, AC 240 V, DC 150 V, 200 kA, BS88, 83 x 84 mm, aR, BS Fuse, Fuse-link, high speed, 400 A, AC 240 V, DC 150 V, BS88, 83 x 84 mm, aR, BS, offset bolted tags, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-0111 Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I]_N 400 A Rated voltage AC 240 V DC 150 V Construction size BS88 Size 83 x 84 mm Utilization category aR Breaking Capacity 200 kA Suitable for size/applications DC common bus, DC drives, power converters/rectifiers and reduced voltage starters Standard/Approval BSS Shape offset bolted tags Standards/Regulations BS88-4 IEC 60269-4 Optional accessories fuse-holder BH-0111 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (
[AFZ800015])Construction sizeOtherRated current400 ARated voltage240 VVoltage typeAC/DCRated switching
capacity200 kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorNoneInsulated
metal gripping lugs (IMGL)No
ETIM for 400LMMT Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 400A 240V THYRISTOR FUSE (1) with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.