

## INDUSTRIAL COMPONENT DATA

# TIA32 EATON ELECTRIC Fuse-link, LV, 32 A, AC 660 V, DC 460 V, BS88/A2, 22 x 86 mm, gL/gG, BS

Brand: EATON - MOELLER | Manufacturer Part Number: TIA32



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | TIA32           |
| Catalog number  | 10000           |
| Category        | HRC fuse        |
| Minimum order   | 20 Pcs          |
| Document ID     | EO-FF7D998D69   |
| Generated       | 2026-08-06      |

## Product Overview

32A 690V AC / 460V DC gG INDUSTRIAL FUSE

Fuse-link, LV, 32 A, AC 660 V, DC 460 V, BS88/A2, 22 x 86 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 32 A, AC 660 V, DC 460 V, BS88/A2, 22 x 86 mm, gL/gG, BS, offset bolted tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder CM32F RS32

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Bussmann Series Low Voltage fuses and accessories

## Additional Product Information

## General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number TIA32 EAN 5027590514224 UPC 051712392921 Product Length/Depth 84.5 mm Product Height 21 mm Product Width 21 mm Product Weight 48.75 g

Compliances Contact Manufacturer Electrical data

Amperage Rating 32 A Voltage rating 690 V Voltage type AC/DC Breaking capacity 80 kA Class Class gG/gL Compatible fuse holder

Suitable for CM32F Camaster fuse holder

RS32 Red spot fuse holder Product specifications

Fuse type TIA Fitted with: Offset bolted tags Construction BS88/A2

ETIM for TIA32 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)  
Fuse system E  
Fuse construction type according to IEC 60269 (EF015865)  
A2  
Type of current (EF000143)  
AC/DC  
Rated voltage AC (EF007682)  
660 V  
Rated voltage DC (EF012281)  
460 V  
Rated current (EF000227)  
32 A  
Utilization category according to IEC 60269 (EF002572)  
gG (cable protection/equipment protection)  
Breaking capacity (EF005617)  
80 kA  
Colour code (EF000931)  
None  
Type of fuse status indicator (EF004473)  
None  
Mounting holes (EF021553)  
M5  
Centre-to-centre distance of connections (EF021151)  
73 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TIA32 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.