

INDUSTRIAL COMPONENT DATA

SRSD1COW 167378 EATON ELECTRIC Distribution board-light intensity switch, 2 TLE, 2-2000 Lux, w. surface moun..

Brand: EATON - MOELLER | Manufacturer Part Number: SRSD1COW



Manufacturer	EATON - MOELLER
MPN / Reference	SRSD1COW
Catalog number	167378
Category	Twilight switch for distribution board
Minimum order	1 Pcs
Document ID	EO-32B4664E71
Generated	2026-08-01

Product Overview

Distribution board-light intensity switch, 2 TLE, 2-2000 Lux, w. surface mounting light sensor

Distribution board-light intensity switch, width 35 mm, separate surface mounting - light sensor (IP 55), brightness range: 2-2000 lux on-/off-delay 60 sec /60 sec., undelayed LED display, duoFix- plug-in terminals, test button, 1 changeover contacts 16A/250V~ with LED sealable transparent cover.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

Distribution board-light intensity switch, 2 TLE, 2-2000 Lux, w. surface mounting light sensor Eaton Catalog No.

SRSD1COW EL-Nummer (Norway) 0001456980 Distribution board-light intensity switch, width 35 mm, separate surface mounting - light sensor (IP 55), brightness range: 2-2000 lux on-/off-delay 60 sec /60 sec., undelayed LED display, duoFix- plug-in terminals, test button, 1 changeover contacts 16A/250V~ with LED sealable transparent cover. [Design verification as per IEC/EN 61439

Rated operational current for specified heat dissipation [In] 0 A Heat dissipation per pole, current-dependent [Pvid] 0 W Equipment heat dissipation, current-dependent [Pvid] 0 W Static heat dissipation, non-current-dependent [Pvs] 1.7 W Heat dissipation capacity [Pdiss] 0 W Operating ambient temperature min. -30 °C Operating ambient temperature max. +55 °C 0 , Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Twilight switch for distribution board (EC001645) Electric

engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Twilight switch for distribution board ( [ACN363011]) Rated voltage 230 V Rated frequency 50 - 60 Hz Max. incandescent lamp load 2300 W Max. load fluorescent lamp 2300 VA Max. load fluorescent lamp (Duo circuit) 2300 VA Max. load fluorescent lamp (parallel compensated) 400 VA Max. switching current (cos phi = 0.6) 0 A Rat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SRSD1COW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.