

INDUSTRIAL COMPONENT DATA

TSDW2CO 167380 EATON ELECTRIC Series connection digital time switch 2 channels, 7 days, text line, push term..

Brand: EATON - MOELLER | Manufacturer Part Number: TSDW2CO



Manufacturer	EATON - MOELLER
MPN / Reference	TSDW2CO
Catalog number	167380
Category	Digital time switch for distribution board
Minimum order	1 Pcs
Document ID	EO-18176BB01E
Generated	2026-07-27

Product Overview

Series connection digital time switch 2 channels, 7 days, text line, push terminal, 2 TLE

Series connection digital time switch with time clock set ex-factory, text-oriented operator prompting in display, interface for memory card, width 35 mm, spring push terminals, 10 years autonomy and programmed DST setting. Day and week program shortest changeover time 1 min., continuous switch ON/OFF/AUTO, switching preselection, 56 memory locations, PIN coding, 2 channels 2 changeover contacts 16A 250V~.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Others and Accessories
--------------	---

Additional Product Information

Series connection digital time switch 2 channels, 7 days, text line, push terminal, 2 TLE Eaton Catalog No. TSDW2CO EL-Nummer (Norway) 0001456982 Series connection digital time switch with time clock set ex-factory, text-oriented operator prompting in display, interface for memory card, width 35 mm, spring push terminals, 10 years autonomy and programmed DST setting. Day and week program shortest changeover time 1 min., continuous switch ON/OFF/AUTO, switching preselection, 56 memory locations, PIN coding, 2 channels 2 changeover contacts 16A 250V~. [Design verification as per IEC/EN 61439

Rated operational current for specified heat dissipation [In] 0 A Heat dissipation per pole, current-dependent [Pvid] 0 W Equipment heat dissipation, current-dependent [Pvid] 0 W Static heat dissipation, non-current-dependent [Pvs] 1.1 W Heat dissipation capacity [Pdiss] 0 W Operating ambient temperature min. -30 °C Operating ambient temperature max. +55 °C 0 , Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Digital time switch for distribution board (EC002305) Electric

engineering, automation, process control engineering / Measurement technology, process measurement technology / Measuring appliance, time / Digital time switch ( [ACN653011]) Mounting method DIN rail Number of channels 2 Supply voltage 230 - 240 V Voltage type of supply voltage AC Frequency supply voltage 50 - 60 Hz Autonomy in hours 0 Autonomy in years 10 Accuracy per...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TSDW2CO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.