

INDUSTRIAL COMPONENT DATA

TSQD1CO 167390 Y7-167390 EATON ELECTRIC Series connection time switch 24 hrs., series connection time switch..

Brand: EATON - MOELLER | Manufacturer Part Number: TSQD1CO



Manufacturer	EATON - MOELLER
MPN / Reference	TSQD1CO
Catalog number	Y7-167390
Category	Analogous time switch for distribution board
Minimum order	1 Pcs
Document ID	EO-48966C8799
Generated	2026-08-02

Product Overview

Series connection time switch 24 hrs., series connection time switch, autonomy, 3 TLE

TSQD1CO

Eaton Distribution parts. Series connection time switch 24 hrs., series connection time switch, autonomy, 3 TLE

Modularly installed time switch with approx. 200 autonomy in hours, width 52.5 mm, 24 hrs. program shortest changeover time 15 min., clock hands for switching the time display and 12h / 24h, clockwise and counterclockwise clock-time correction possible, switching preselection, switching by hand with 3 positions: duration ON / AUTO / OFF permanently, switch-status display, duoFix spring plug-in terminal for 2 conductor each, 1 changeover contacts 16A/250V~, 230V /45-50 Hz sealable transparent cover.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Others and Accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 167390 Model Code TSQD1CO EAN 4015081639205 Product Length/Depth 65.6 mm Product Height 90 mm Product Width 54 mm Product Weight 0.12 kg Compliances RoHS conform Product specifications

Mounting method DIN rail Equipment heat dissipation, current-dependent 0 W Number of channels 1 Accuracy per day 1 s Ambient operating temperature - max 55 °C Ambient operating temperature - min -20 °C Autonomy in hours 200 hour

Autonomy in years 0 year Frequency supply voltage - max 60 Hz Frequency supply voltage - min 45 Hz Heat dissipation capacity 0 W Heat dissipation per pole, current-dependent 0 W Nominal switching current at 250 V AC 16 A Contact type Change-over contact Degree of protection IP20 Functions Potential free switch contact
Switching preselection
24 h program
Quartz controlled
Manual operation Voltage type AC Shortest switching time at channel 1 15 min Shortest switching time at channel 2 0 min
Program shift divide 1 15 min Program shift divide 2 0 min Rated operational current for specified heat dissipation (In) 0 A
Switching power LED - max 600 W Static heat dissipation, non-current-dependent 0.5 W Supply voltage - max 230 V
Supply voltage - min 110 V Width in number of modular spacings 3
ETIM for 167390 Modular devices for distribution board/surface mounting (EC002304)
Feature Name
Feature Value
Mounting method (EF000003)
DIN rail
Number of channels (EF000259)
1
Supply voltage (EF004127)
110 V
Vol...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TSQD1CO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.