

INDUSTRIAL COMPONENT DATA

**DILM32-XTED11-100(RAC240) 104948 Y7-104948 EATON
ELECTRIC Timer module, 200-240VAC, 5-100s, off-delayed**

Brand: EATON - MOELLER | Manufacturer Part Number: DILM32-XTED11-100(RAC240)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM32-XTED11-100(RAC240)
Catalog number	Y7-104948
Category	Timer block
Minimum order	1 Pcs
Document ID	EO-28B5A3E553
Generated	2026-08-02

Product Overview

Timer module, 200-240VAC, 5-100s, off-delayed

DILM32-XTED11-100(RAC240)

Eaton Moeller® series DILM Timer module, 200-240VAC, 5-100s, off-delayed

Timer module, Off-delayed, auxiliary voltage-free, Cannot be combined with top mounting auxiliary contacts, Incl. suppressor circuits, Product range: Accessories, Time range: 5 - 100 s, Mounting position: As required, except suspended, Degree of Protection: IP20, Weight: 0.08 kg, For use with: DILM7 - DILM38, DILMP20, DILMP32-DILMP45, DILA, DILMF7, DILMF11, DILMF14, DILMF25, DILMF32, Standards DIN EN 61812, IEC/EN 60947, VDE 0660, UL, CSA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM timer module Catalog Number 104948 Model Code

DILM32-XTED11-100(RAC240) EAN 4015081048069 Product Length/Depth 86 mm Product Height 38 mm Product Width 45 mm Product Weight 0.073 kg Certifications CSA Class No.: 3211-03

IEC/EN 60947

CSA File No.: 012528

UL File No.: E29184

UL

CE

CSA-C22.2 No. 14-05

IEC/EN 60947-4-1

UL 508

DIN EN 61812

CSA

VDE 0660

UL Category Control No.: NKCR Catalog Notes Cannot be combined with top mounting auxiliary contacts Features & Functions

Fitted with: Suppressor circuits Operating mode Electronic General

Delay time 200 ms, Off-delayed

50 ms, On-delayed Lifespan, mechanical 3,000,000 Operations (DC operated)

3,000,000 Operations (AC operated) Operating frequency 360 mechanical Operations/h

3600 Operations/h Overvoltage category III Pollution degree 3 Product category Accessories Protection Finger and

back-of-hand proof, Protection against direct contact when actuated from front Rated impulse withstand voltage (Uimp)

4000 V AC Recovery time 70 ms (after 100 % time delay) Ambient conditions, mechanical

Mounting position As required (except suspended) Shock resistance 6 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

6 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms Climatic environmental conditions

Ambient operating temperature - min -25 °F Ambient operating temperature - max 60 °F Ambient....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM32-XTED11-100(RAC240) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.